

Starter kit - NLC-START-02 - 2701425

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



24 V DC base unit with PNP transistor outputs, LCD display, USB module, serial cable, input and output simulators and Quick Start Guide

Product Description


Kit containing items required to start programming and testing the Nanoline family of controllers.

Your advantages

- Basic unit
- USB cable
- Output simulator (available as 24 V AC or 24 V DC model)
- Input simulator (available as 24 V AC or 24 V DC model)
- Operator panel



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 325530
GTIN	4046356325530
Weight per Piece (excluding packing)	808.300 g
Custom tariff number	85371098
Country of origin	India

Technical data

Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50

Starter kit - NLC-START-02 - 2701425

Technical data

Environmental Product Compliance

	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
--	---

Articles in set

Base unit - NLC-050-024D-06I-04QTP-00A - 2701027



24 V DC Nanoline base unit. Equipped with 6 digital input and 4 PNP digital output channels. Additional I/O channels can be added using a maximum of three I/O extension modules. Optional communication modules provide network or serial connectivity. Optional Operator Panel provides user interface. Programming is via nanoNavigator.

Operator terminal - NLC-OP1-LCD-032-4X20 - 2701137



User interface for Nanoline controllers. Mounts directly on the base unit. Can be mounted remotely using the mounting kit.

nanoLC module - NLC-MOD-USB - 2701195



Serial connection to PC's USB port for data transfer or software configuration

Cable - NLC-PC/USB-CBL 2M - 2701247



Cable, serial

Starter kit - NLC-START-02 - 2701425

Articles in set

Simulator card - NLC-050-24DC-IN-SIM - 2701357

Card to simulate inputs on an Nanoline base unit



Simulator card - NLC-050-24DC-OUT-SIM-T - 2701360

Card to simulate transistor outputs on a Nanoline base unit



Classifications

eCl@ss

eCl@ss 4.0	27250300
eCl@ss 4.1	27250300
eCl@ss 5.0	27242700
eCl@ss 5.1	27242700
eCl@ss 6.0	27242200
eCl@ss 7.0	27242216
eCl@ss 8.0	27242216
eCl@ss 9.0	27242216

ETIM

ETIM 2.0	EC001417
ETIM 3.0	EC001417
ETIM 4.0	EC001417
ETIM 5.0	EC001417
ETIM 6.0	EC001417
ETIM 7.0	EC001417

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015

Starter kit - NLC-START-02 - 2701425

Classifications

UNSPSC

UNSPSC 12.01	43201404
UNSPSC 13.2	39122329