


H0,25/12T GE



Similar to illustration

General ordering data

Type	H0,25/12T GE
Order No.	9021020000
Version	Wire end ferrule, insulated, 10 mm, 8 mm, Yellow
GTIN (EAN)	4008190184230
Qty.	500 pc(s).
Packaging	loose

Dimensions and weights

Width	12 mm
Width (inches)	0.472 inch
Net weight	0.052 g

Technical data

Version	insulated
---------	-----------

Wire-end ferrules

Collar diameter (D2)	1.8 mm
Colour code	Telemecanique
Conductor cross-section	0.25 mm ²
Contact surface diameter (D1)	0.8 mm
Contact surface length (L2)	8 mm
L1 in mm	12 mm
Metal sleeve thickness (S1)	0.15 mm

Plastic collar thickness (S2)	0.25 mm
Stripping length	10 mm
Wire connection cross section AWG, max.	AWG 24

Downloads

Brochure/Catalogue	CAT 6 TOOLS 15/16 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S

Classifications

ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005
ETIM 6.0	EC000005
UNSPSC	31-16-31-02
eClass 5.1	27-40-02-01
eClass 6.2	27-40-02-01
eClass 7.1	27-40-02-01
eClass 8.1	27-40-02-01
eClass 9.0	27-40-02-01
eClass 9.1	27-40-02-01

Approvals

Approvals	
ROHS	Conform
UL File Number Search	E354986

Related products:

Type: H0,25/10 HBL	Version:
Order No.: 9025740000	Wire end ferrule, insulated, 8 mm, 6 mm, Light Blue
Description of article: Wire end ferrule with plastic collar, light blue	

[PDF data sheet](#) [Add to Inquiry List](#)

Type: H0,25/10T GE	Version:
Order No.: 9021010000	Wire end ferrule, insulated, 8 mm, 6 mm, Yellow
Description of article: Wire end ferrule with plastic collar, yellow	

[PDF data sheet](#) [Add to Inquiry List](#)

Type: H0,25/12 HBL

Version:

Order No.: 9025760000

Wire end ferrule, insulated, 10 mm, 8 mm, Light Blue

Description of article: Wire end ferrule with plastic collar, light blue

[PDF data sheet](#) [Add to Inquiry List](#)