



JKL PART NUMBER	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4320-27B	x = .293 y = .293	@ 0° C 1300	@ 25° C 545	5 ± 1	14400	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

	METRIC	DIMENSIONS ARE IN MILLIMETERS						
	THIRD ANGLE PROJECTION	TOLERANCE UNLESS OTHERWISE SPECIFIED						TITLE
		1 PL +/- 0		SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP				
		2 PL +/- 0		SIZE	FSCM NO.	DRAWING NO.	BF4320-27B	
		ANGLE +/- 0		A	55335			
	RELEASED AND CANCEL P-0210-03	12/9/02		SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING -	NONE	12/9/02			1 of 1
			MANUAL REVISIONS NOT PERMITTED					