



JKL LAMP PART NO.	COLOR GREEN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) (AVG.)
BF20100-11B	x = 0.318±0.03 y = 0.556±0.03	780 @ 0°C	260	5	40,000 REF.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED		JKL COMPONENTS CORPORATION					
				1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
A			DRAWN BY L. WENGSTROM	APPV'D BY J.K.	DATE 3/15/04	SIZE A	FSCM NO. 55335	DRAWING NO. BF20100-11B			
DIMENSION CHANGES			3/15/04								
RELEASE			3/10/04								
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 3/10/04	REVISION DATE 3/15/04	REV. NO. A	SHEET 1 OF 1	