



Specation

Material: Nylon 66 UL 94V-2

Poles	Dimension mm (in.)		Part No.
	A	B	
2	2.54 (0.100)	5.64 (0.222)	MK-H-02
3	5.08 (0.200)	8.16 (0.321)	MK-H-03
4	7.62 (0.300)	10.72 (0.422)	MK-H-04
5	10.16 (0.400)	13.30 (0.524)	MK-H-05
6	12.70 (0.500)	15.78 (0.621)	MK-H-06
7	15.24 (0.600)	18.40 (0.724)	MK-H-07
8	17.78 (0.700)	20.80 (0.819)	MK-H-08
9	20.32 (0.800)	23.50 (0.925)	MK-H-09
10	22.86 (0.900)	26.00 (1.024)	MK-H-10
11	25.40 (1.000)	28.50 (1.122)	MK-H-11
12	27.94 (1.100)	31.00 (1.220)	MK-H-12
13	30.48 (1.200)	33.50 (1.319)	MK-H-13
14	32.02 (1.300)	36.00 (1.417)	MK-H-14
15	35.56 (1.400)	38.50 (1.516)	MK-H-15
16	38.10 (1.500)	41.20 (1.622)	MK-H-16
17	40.64 (1.600)	43.60 (1.717)	MK-H-17
18	43.18 (1.700)	46.32 (1.824)	MK-H-18
19	45.72 (1.800)	48.80 (1.921)	MK-H-19
20	48.26 (1.900)	51.34 (2.021)	MK-H-20

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫有限公司

PART NO. MK-H-xx

DWG NO. MK-H-xx

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.5

.XX ± 0.1

.XXX

AWG

DESCRIPTION:

2.54mm Wire-to-Board HOUSING

AREA

REVISIONS

HK

DATE