



November 1988
Revised November 1999

74AC08 • 74ACT08

Quad 2-Input AND Gate

General Description

The AC/ACT08 contains four, 2-input AND gates.

Features


- I_{CC} reduced by 50% on 74AC only
- Outputs source/sink 24 mA

Ordering Code:


Order Number	Package Number	Package Description
74AC08SC	M14A	14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-120, 0.150" Narrow Body
74AC08SJ	M14D	14-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
74AC08MTC	MTC14	14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
74AC08PC	N14A	14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
74ACT08SC	M14A	14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-120, 0.150" Narrow Body
74ACT08MTC	MTC14	14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
74ACT08PC	N14A	14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide

Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering code. (PC not available in Tape and Reel.)

Logic Symbol



Connection Diagram



Pin Descriptions

Pin Names	Description
A_n, B_n O_n	Inputs Outputs

FACT™ is a trademark of Fairchild Semiconductor Corporation.

Absolute Maximum Ratings(Note 1)

Supply Voltage (V_{CC})	–0.5V to +7.0V		
DC Input Diode Current (I_{IK})			
$V_I = -0.5V$	–20 mA	AC	2.0V to 6.0V
$V_I = V_{CC} + 0.5V$	+20 mA	ACT	4.5V to 5.5V
DC Input Voltage (V_I)	–0.5V to $V_{CC} + 0.5V$		
DC Output Diode Current (I_{OK})			
$V_O = -0.5V$	–20 mA	Input Voltage (V_I)	0V to V_{CC}
$V_O = V_{CC} + 0.5V$	+20 mA	Output Voltage (V_O)	0V to V_{CC}
DC Output Voltage (V_O)	–0.5V to $V_{CC} + 0.5V$		
DC Output Source or Sink Current (I_O)			
DC V_{CC} or Ground Current per Output Pin (I_{CC} or I_{GND})	±50 mA	Operating Temperature (T_A)	–40°C to +85°C
Storage Temperature (T_{STG})	–65°C to +150°C	Minimum Input Edge Rate ($\Delta V/\Delta t$)	
Junction Temperature (T_J)		AC Devices	
PDIP	140°C	V_{IN} from 30% to 70% of V_{CC}	
		V_{CC} @ 3.3V, 4.5V, 5.5V	125 mV/ns
		ACT Devices	
		V_{IN} from 0.8V to 2.0V	
		V_{CC} @ 4.5V, 5.5V	125 mV/ns

Recommended Operating Conditions

Supply Voltage (V_{CC})			
AC	2.0V to 6.0V		
ACT	4.5V to 5.5V		
Input Voltage (V_I)	0V to V_{CC}		
Output Voltage (V_O)	0V to V_{CC}		
Operating Temperature (T_A)	–40°C to +85°C		
Minimum Input Edge Rate ($\Delta V/\Delta t$)			
AC Devices			
V_{IN} from 30% to 70% of V_{CC}			
V_{CC} @ 3.3V, 4.5V, 5.5V	125 mV/ns		
ACT Devices			
V_{IN} from 0.8V to 2.0V			
V_{CC} @ 4.5V, 5.5V	125 mV/ns		

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. Fairchild does not recommend operation of FACT™ circuits outside databook specifications.

DC Electrical Characteristics for AC

Symbol	Parameter	V_{CC} (V)	$T_A = +25^\circ C$		Units	Conditions
			Typ	Guaranteed Limits		
V_{IH}	Minimum HIGH Level	3.0	1.5	2.1	V	$V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$
	Input Voltage	4.5	2.25	3.15		
V_{IL}	Maximum LOW Level	3.0	1.5	0.9	V	$V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$
	Input Voltage	4.5	2.25	1.35		
V_{OH}	Minimum HIGH Level	3.0	2.99	2.9	V	$I_{OUT} = -50 \mu A$
	Output Voltage	4.5	4.49	4.4		
		5.5	5.49	5.4		
		3.0		2.56	V	$V_{IN} = V_{IL}$ or V_{IH} $I_{OH} = -12 mA$ $I_{OH} = -24 mA$ $I_{OH} = -24 mA$ (Note 2)
V_{OL}	Maximum LOW Level	4.5	3.86	3.76		
	Output Voltage	5.5	4.86	4.76		
		3.0		0.36	V	$V_{IN} = V_{IL}$ or V_{IH} $I_{OL} = 12 mA$ $I_{OL} = 24 mA$ $I_{OL} = 24 mA$ (Note 2)
		4.5		0.44		
I_{IN} (Note 4)	Maximum Input Leakage Current	5.5		±0.1	μA	$V_I = V_{CC}$; GND
				±1.0		
I_{OLD}	Minimum Dynamic Output Current (Note 3)	5.5			mA	$V_{OLD} = 1.65V$ Max
I_{OHD}		5.5		75	mA	$V_{OHD} = 3.85V$ Min
I_{CC} (Note 4)	Maximum Quiescent Supply Current	5.5		2.0	20.0	μA
						$V_{IN} = V_{CC}$ or GND

Note 2: All outputs loaded; thresholds on input associated with output under test.

Note 3: Maximum test duration 2.0 ms, one output loaded at a time.

Note 4: I_{IN} and I_{CC} @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V V_{CC} .

DC Electrical Characteristics for ACT

Symbol	Parameter	V _{CC} (V)	T _A = +25°C		Units	Conditions
			Typ	Guaranteed Limits		
V _{IH}	Minimum HIGH Level Input Voltage	4.5 5.5	1.5 1.5	2.0 2.0	2.0 2.0	V V _{OUT} = 0.1V or V _{CC} - 0.1V
V _{IL}	Maximum LOW Level Input Voltage	4.5 5.5	1.5 1.5	0.8 0.8	0.8 0.8	V V _{OUT} = 0.1V or V _{CC} - 0.1V
V _{OH}	Minimum HIGH Level Output Voltage	4.5 5.5	4.49 5.49	4.4 5.4	4.4 5.4	V I _{OUT} = -50 μA
		4.5 5.5		3.86 4.86	3.76 4.76	V V _{IN} = V _{IL} or V _{IH} I _{OH} = -24 mA I _{OH} = -24 mA (Note 5)
		4.5 5.5		0.1 0.1	0.1 0.1	V I _{OUT} = 50 μA
V _{OL}	Maximum LOW Level Output Voltage	4.5 5.5	0.001 0.001	0.36 0.36	0.44 0.44	V V _{IN} = V _{IL} or V _{IH} I _{OL} = 24 mA I _{OL} = 24 mA (Note 5)
		4.5 5.5		0.36 0.36	0.44 0.44	V
I _{IN}	Maximum Input Leakage Current	5.5		±0.1	±1.0	μA V _I = V _{CC} , GND
I _{CCT}	Maximum I _{CC} /Input	5.5	0.6		1.5	mA V _I = V _{CC} - 2.1V
I _{OLD}	Minimum Dynamic Output Current (Note 6)	5.5			75	mA V _{OLD} = 1.65V Max
		5.5			-75	mA V _{OLD} = 3.85V Min
I _{CC}	Maximum Quiescent Supply Current	5.5		4.0	40.0	μA V _{IN} = V _{CC} or GND

Note 5: All outputs loaded; thresholds on input associated with output under test.

Note 6: Maximum test duration 2.0 ms, one output loaded at a time.

AC Electrical Characteristics for AC

Symbol	Parameter	V _{CC} (V) (Note 7)	T _A = +25°C C _L = 50 pF			Units	
			T _A = -40°C to +85°C C _L = 50 pF				
			Min	Typ	Max		
t _{PLH}	Propagation Delay	3.3 5.0	1.5 1.5	7.5 5.5	9.5 7.5	ns	
t _{PHL}	Propagation Delay	3.3 5.0	1.5 1.5	7.0 5.5	8.5 7.0	ns	

Note 7: Voltage Range 3.3 is 3.3V ± 0.3V

Voltage Range 5.0 is 5.0V ± 0.5V

AC Electrical Characteristics for ACT

Symbol	Parameter	V _{CC} (V) (Note 8)	T _A = +25°C C _L = 50 pF			Units	
			T _A = -40°C to +85°C C _L = 50 pF				
			Min	Typ	Max		
t _{PLH}	Propagation Delay	5.0	1.0	6.5	9.0	ns	
t _{PHL}	Propagation Delay	5.0	1.0	6.5	9.0	ns	


Note 8: Voltage Range 5.0 is 5.0V ± 0.5V

Capacitance




Symbol	Parameter	Typ	Units	Conditions
C _{IN}	Input Capacitance	4.5	pF	V _{CC} = OPEN
C _{PD}	Power Dissipation Capacitance	20.0	pF	V _{CC} = 5.0V

Physical Dimensions




inches (millimeters) unless otherwise noted



14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-120, 0.150" Narrow Body
Package Number M14A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)LAND PATTERN RECOMMENDATION


DIMENSIONS ARE IN MILLIMETERS








NOTES:

- A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M14DRevB1




14-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
Package Number M14D

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)LAND PATTERN RECOMMENDATIONDETAIL A

14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
Package Number MTC14

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



**14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
Package Number N14A**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com