

GD54/74HC151, GD54/74HCT151

8-TO-1 LINE DATA SELECTOR/MUX


General Description

These devices are identical in pinout to the 54/74LS151. This circuit selects one of the 8 binary data inputs, depending on the address presented on the A, B, and C inputs. It features both true(Y) and complementary(\bar{Y}) outputs. The enable input must be at a low logic level to enable the multiplexing. A high logic level at the enable pin forces the Y output high and the \bar{Y} output low. The HC/HCT 151 is similar in function to the HC/HCT 251 which has 3-state outputs. These devices are characterized for operation over wide temperature ranges to meet industry and military specifications.

Features

- Low Power consumption characteristic of CMOS devices
- Output drive capability: 10 LS TTL Loads Min.
- Operating speed superior to LS TTL
- Wide operating voltage range: for HC 2 to 6 volts for HCT 4.5 to 5.5 volts
- Low input current: 1 μ A Max.
- Low quiescent current: 80 μ A Max. (74HC)
- High noise immunity characteristic of CMOS
- Diode protection on all inputs

Pin Configuration



Suffix-Blank : Plastic Dual In Line Package
 Suffix-J : Ceramic Dual In Line Package
 Suffix-D : Small Outline Package

Function Table

INPUTS												OUTPUTS		
E	C	B	A	I ₀	I ₁	I ₂	I ₃	I ₄	I ₅	I ₆	I ₇	\bar{Y}	Y	
H	X	X	X	X	X	X	X	X	X	X	X	X	H	L
L	L	L	L	L	X	X	X	X	X	X	X	X	H	L
L	L	L	H	X	X	X	X	X	X	X	X	X	L	H
L	L	L	H	X	L	X	X	X	X	X	X	X	H	L
L	L	L	H	X	H	X	X	X	X	X	X	X	L	H
L	L	H	L	X	X	L	X	X	X	X	X	X	H	L
L	L	H	L	X	X	H	X	X	X	X	X	X	L	H
L	L	H	H	X	X	X	L	X	X	X	X	X	H	L
L	L	H	H	X	X	X	H	X	X	X	X	X	L	H
L	H	L	L	X	X	X	X	L	X	X	X	X	H	L
L	H	L	L	X	X	X	X	H	X	X	X	X	L	H
L	H	L	H	X	X	X	X	X	L	X	X	X	H	L
L	H	L	H	X	X	X	X	X	H	X	X	X	L	H
L	H	H	L	X	X	X	X	X	X	L	X	X	H	L
L	H	H	L	X	X	X	X	X	X	H	X	X	L	H
L	H	H	H	X	X	X	X	X	X	X	X	X	H	L
L	H	H	H	X	X	X	X	X	X	X	X	X	H	L

H = HIGH voltage level

L = LOW voltage level

X = don't care

Absolute Maximum Ratings

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CC}	DC Supply voltage		-0.5	+7	V
I_{IK}, I_{OK}	DC input or output diode current	for $V_i < -0.5$ or $V_o > V_{CC} + 0.5V$		20	mA
I_O	DC output source or sink current	for $-0.5V < V_o < V_{CC} + 0.5V$		35	mA
I_{CC}	DC V_{CC} or GND current			30	mA
T_{stg}	Storage temperature range		-65	150	°C
P_D	Power dissipation per package	above +70°C; degrade linearly with 8mW/K		500	mW
T_L	Lead temperature	At distance $1/16 \pm 1/32$ in. from case for 60 sec(CERAMIC) 10 sec(PLASTIC)		300 260	°C

Recommended Operating Conditions

CHARACTERISTIC	LIMITS		UNITS
	MIN.	MAX.	
Supply-Voltage Range V_{CC} : GD54/74HC Types GD54/74HCT Types	2 4.5	6 5.5	V
DC Input or Output Voltage V_i, V_o	0	V_{CC}	V
Operating Temperature T_A : GD74 Types GD54 Types	-40 -55	+85 +125	°C
Input Rise and Fall times t_r, t_f : GD54/74HC Types at 2V at 4.5V at 6V GD54/74HCT Types at 4.5 V		1000 500 400 500	ns


Logic Diagram

Fig. 1 Logic diagram

DC Electrical Characteristics for HC

SYMBOL	PARAMETER	TEST CONDITION	V _{CC} (V)	T _A =25°C			GD74HC151		GD54HC151		UNIT
				MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
V _{IH}	HIGH level input Voltage			2.0 4.5 6.0	1.5 3.15 4.2		1.5 3.15 4.2		1.5 3.15 4.2		V
V _{IL}	LOW level input voltage			2.0 4.5 6.0			0.3 0.9 1.2		0.3 0.9 1.2		V
V _{OH}	HIGH level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OH} =-20µA	2.0 4.5 6.0	1.9 4.4 5.9	2.0 4.5 6.0		1.9 4.4 5.9		1.9 4.4 5.9	V
			I _{OH} =-4mA I _{OH} =-5.2mA	4.5 6.0	3.98 5.48	4.3 5.2		3.84 5.34		3.7 5.2	
V _{OL}	LOW level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OL} =20µA	2.0 4.5 6.0			0.1 0.1 0.1		0.1 0.1 0.1		V
			I _{OL} =4mA I _{OL} =5.2mA	4.5 6.0		0.17 0.15	0.26 0.26		0.33 0.33		
I _{IN}	Input leakage Current	V _{IN} =V _{CC} or GND		6.0			0.1		1.0		1.0 µA
I _{CC}	Quiescent Supply Current	V _{IN} =V _{CC} or GND I _{out} =0µA		6.0			8		80		160 µA

DC Electrical Characteristics for HCT

SYMBOL	PARAMETER	TEST CONDITION	V _{CC} (V)	T _A =25°C			GD74HCT151		GD54HCT151		UNIT
				MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
V _{IH}	HIGH level input Voltage		4.5 to 5.5	2.0			2.0		2.0		V
V _{IL}	LOW level input voltage		4.5 to 5.5				0.8		0.8		V
V _{OH}	HIGH level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OH} =-20µA	4.5	4.4	4.5		4.4		4.4	V
			I _{OH} =-4mA	4.5	3.98	4.3		3.84		3.7	
V _{OL}	LOW level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OL} =20µA	4.5			0.1		0.1		V
			I _{OL} =4mA	4.5		0.17	0.26		0.33		
I _{IN}	Input leakage Current	V _{IN} =V _{CC} or GND	5.5				0.1		1.0		1.0 µA
I _{CC}	Quiescent Supply Current	V _{IN} =V _{CC} or GND I _{out} =0µA	5.5				8		80		160 µA

AC Characteristics for HC: $t_r=t_f=6\text{ns}$ $C_L=50\text{ pF}$

SYMBOL	PARAMETER	V_{CC} (V)	$T_A=25^\circ C$			GD74HC151		GD54HC151		UNIT
			MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
t_{PLH}/t_{PHL}	Propagation Delay Time A,B,C to Y, \bar{Y}	2.0		52	170		215		255	ns
		4.5		19	34		43		51	
		6.0		15	29		37		43	
t_{PLH}/t_{PHL}	Propagation Delay Time In to Y, \bar{Y}	2.0		52	170		215		225	ns
		4.5		19	34		43		51	
		6.0		15	29		37		43	
t_{PLH}/t_{PHL}	Propagation Delay Time \bar{E} to Y, \bar{Y}	2.0		41	145		180		220	ns
		4.5		15	29		36		44	
		6.0		12	25		31		38	
t_{TLH}/t_{THL}	Output Transition Time	2.0		19	75		95		110	ns
		4.5		7	15		19		22	
		6.0		6	13		16		19	

AC Characteristics for HCT: $t_r=t_f=6\text{ns}$ $C_L=50\text{ pF}$

SYMBOL	PARAMETER	V_{CC} (V)	$T_A=25^\circ C$			GD74HCT151		GD54HCT151		UNIT
			MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
t_{PLH}/t_{PHL}	Propagation Delay Time A,B,C to Y, \bar{Y}	4.5		20	38		48		57	ns
t_{PLH}/t_{PHL}	Propagation Delay Time In to Y, \bar{Y}	4.5		20	38		44		57	ns
t_{PLH}/t_{PHL}	Propagation Delay Time \bar{E} to Y, \bar{Y}	4.5		21	40		51		62	ns
t_{TLH}/t_{THL}	Output Transition Time	4.5		7	15		19		22	ns

AC Waveforms




Fig. 2 Waveforms showing the multiplexer input (In) to outputs (Y and \bar{Y}) propagation delays and the output transition times.




Fig. 3 Waveforms showing the select input (A.B.C) and enable input (\bar{E}) to outputs (Y and \bar{Y}) propagation delays and the output transition times.

Note to AC waveforms

(1) HC : $V_M=50\text{s}$; $V_i=\text{GND}$ to V_{CC} .

HCT : $V_M=1.3\text{V}$; $V_i=\text{GND}$ to 3V .