

SN54F08, SN74F08
QUADRUPLE 2-INPUT POSITIVE-AND GATES

D2932, MARCH 1987—REVISED JANUARY 1989

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

description


These devices contain four independent 2-input AND gates. They perform the Boolean functions $Y = A \cdot B$ or $Y = \bar{A} + \bar{B}$ in positive logic.

The SN54F08 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74F08 is characterized for operation from 0°C to 70°C .

FUNCTION TABLE (each gate)

| INPUTS | OUTPUT | |
|--------|--------|---|
| A | B | Y |
| H | H | H |
| L | X | L |
| X | L | L |

logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for D, J, and N packages.

SN54F08 . . . J PACKAGE

SN74F08 . . . D OR N PACKAGE


(TOP VIEW)



T-43-15

SN54F08 . . . FK PACKAGE

(TOP VIEW)




2

Data Sheets

NC—No internal connection

logic diagram (positive logic)



UNLESS OTHERWISE NOTED this document contains PRODUCTION DATA information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1987, Texas Instruments Incorporated

2-9

TEXAS
INSTRUMENTS

POST OFFICE BOX 655012 • DALLAS, TEXAS 75285

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

| | | |
|---|---------|---------------------------|
| Supply voltage, V _{CC} | | -0.5 V to 7 V |
| Input voltage [†] | | -1.2 V to 7 V |
| Input current | | -30 mA to 5 mA |
| Voltage applied to any output in the high state | | -0.5 V to V _{CC} |
| Current into any output in the low state | | 40 mA |
| Operating free-air temperature range: SN54F08 | | -55°C to 125°C |
| | SN74F08 | 0°C to 70°C |
| Storage temperature range | | -65°C to 150°C |

[†]The input voltage ratings may be exceeded provided the input current ratings are observed.

recommended operating conditions

| | SN54F08 | | | SN74F08 | | | UNIT |
|---|---------|-----|-----|---------|-----|-----|------|
| | MIN | NOM | MAX | MIN | NOM | MAX | |
| V _{CC} Supply voltage | 4.5 | 5 | 5.5 | 4.5 | 5 | 5.5 | V |
| V _{IH} High-level input voltage | 2 | | | 2 | | | V |
| V _{IL} Low-level input voltage | | | | 0.8 | | | V |
| I _{IK} Input clamp current | | | | -18 | | | mA |
| I _{OH} High-level output current | | | | -1 | | | mA |
| I _{OL} Low-level output current | | | | 20 | | | mA |
| T _A Operating free-air temperature | -55 | 125 | 0 | 0 | 70 | | °C |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | SN54F08 | | | SN74F08 | | | UNIT |
|------------------------------|--|---------|------------------|------|---------|------------------|------|------|
| | | MIN | TYP [‡] | MAX | MIN | TYP [‡] | MAX | |
| V _{IK} | V _{CC} = 4.5 V, I _O = -18 mA | | | -1.2 | | | -1.2 | V |
| V _{OH} | V _{CC} = 4.5 V, I _{OH} = -1 mA | 2.5 | 3.4 | | 2.5 | 3.4 | | V |
| | V _{CC} = 4.75 V, I _{OH} = -1 mA | | | 2.7 | | | | |
| V _{OL} | V _{CC} = 4.5 V, I _{OL} = 20 mA | | 0.30 | 0.5 | 0.30 | 0.5 | | V |
| I _I | V _{CC} = 5.5 V, V _I = 7 V | | | 0.1 | | | 0.1 | mA |
| I _{IH} | V _{CC} = 5.5 V, V _I = 2.7 V | | | 20 | | | 20 | μA |
| I _{IL} | V _{CC} = 5.5 V, V _I = 0.5 V | | | -0.6 | | | -0.6 | mA |
| I _{OS} [§] | V _{CC} = 5.5 V, V _O = 0 | -60 | -150 | -60 | -150 | | | mA |
| I _{CCH} | V _{CC} = 5.5 V, V _I = 4.5 V | | 5.5 | 8.3 | 5.5 | 8.3 | | mA |
| I _{CCL} | V _{CC} = 5.5 V, V _I = 0 | | 8.6 | 12.9 | 8.6 | 12.9 | | mA |

switching characteristics (see Note 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | V _{CC} = 5 V, C _L = 50 pF, R _L = 500 Ω, T _A = 25°C | V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω, T _A = MIN to MAX ¹ | UNIT | | | |
|------------------|-----------------|----------------|---|---|------|-----|-----|----|
| | | | 'FO8 | SN54F08 | | | | |
| | | | MIN | TYP | MAX | MIN | MAX | |
| t _{PLH} | A or B | Y | 2.2 | 3.8 | 5.6 | 1.7 | 2.2 | ns |
| t _{PHL} | A or B | Y | 1.7 | 3.6 | 5.3 | 1.2 | 1.7 | ns |

^fAll typical values are at $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$.

5 No more than one output should be shorted at a time and the duration of the short circuit should not exceed one second.

1 For conditions shown as MIN or MAX, use the appropriate value specified under Recommended Operating Conditions.

NOTE 1: Load circuits and waveforms are shown in Section 1.

9



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265