

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

description


These devices contain three independent 3-input AND gates. They perform the Boolean functions $Y = A \cdot B \cdot C$ or $Y = \overline{A} + \overline{B} + \overline{C}$ positive logic.

The SN54F11 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74F11 is characterized for operation from 0°C to 70°C .

FUNCTION TABLE (each gate)

FUNCTION TABLE (each gate)			
INPUTS	OUTPUT		
A	B	C	Y
H	H	H	H
L	X	X	L
X	L	X	L
X	X	L	L

logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.


Pin numbers shown are for D, J, and N packages.

**SN54F11 . . . J PACKAGE
SN74F11 . . . D OR N PACKAGE**

(TOP VIEW)




**SN54F11 . . . FK PACKAGE
(TOP VIEW)**



NC—No internal connection

logic diagram (positive logic)



2

Data Sheets

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V _{CC}	-0.5 V to 7 V
Input voltage [†]	-1.2 V to 7 V
Input current	-30 mA to 5 mA
Voltage applied to any output in the high state	-0.5 V to V _{CC}
Current into any output in the low state	40 mA
Operating free-air temperature range:	SN54F11	-55°C to 125°C
	SN74F11	0°C to 70°C
Storage temperature range	-65°C to 150°C

[†]The input voltage ratings may be exceeded provided the input current ratings are observed.

recommended operating conditions

		SN54F11			SN74F11			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V _{IH}	High-level input voltage		2			2		V
V _{IL}	Low-level input voltage			0.8			0.8	V
I _{IK}	Input clamp current			-18			-18	mA
I _{OH}	High-level output current			-1			-1	mA
I _{OL}	Low-level output current			20			20	mA
T _A	Operating free-air temperature	-55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54F11			SN74F11			UNIT
		MIN	TYP ^S	MAX	MIN	TYP ^S	MAX	
V _{IK}	V _{CC} = 4.5 V, I _I = -18 mA		-1.2			-1.2		V
V _{OH} #	V _{CC} = 4.5 V, I _{OH} = -1 mA	2.5	3.4		2.5	3.4		V
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 20 mA		0.30	0.5		0.30	0.5	V
I _I	V _{CC} = 5.5 V, V _I = 7 V		0.1			0.1		mA
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V		20			20		μA
I _{IL}	V _{CC} = 5.5 V, V _I = 0.5 V		-0.6			-0.6		mA
I _{OS} [¶]	V _{CC} = 5.5 V, V _O = 0	-60	-150	-60	-150	-150	-150	mA
I _{CCH}	V _{CC} = 5.5 V, V _I = 4.5 V		4.1	6.2		4.1	6.2	mA
I _{CCI}	V _{CC} = 5.5 V V _I = 0		6.5	9.7		6.5	9.7	mA

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 5 V, C _L = 50 pF, R _L = 500 Ω, T _A = 25°C	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω, T _A = MIN to MAX‡				UNIT		
			'F11		SNS54F11		SN74F11			
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t _{PLH}	A or B	Y	2.2	3.8	5.6	1.7	7.5	2.2	6.6	ns
t _{PHL}	A or B	Y	1.7	3.7	5.5	1.2	7.5	1.7	6.5	ns

For conditions shown as MIN or MAX, use the appropriate value specified under Recommended Operating Conditions.

§ All typical values are at $V_{CC} = 5\text{ V}$, $T_A = 25^\circ\text{C}$.

1 Not more than one output should be shorted at a time and the duration of the short circuit should not exceed one second.

For the SN74E11 at $V_{CC} = 4.75\text{ V}$ and $I_{OH} = -1\text{ mA}$, $V_{OH\ min} = 2.7\text{ V}$.

NOTE 1: See General Information for load circuits and waveforms.