

**SN54ALS29821, SN54ALS29822
SN74ALS29821, SN74ALS29822
10-BIT BUS INTERFACE FLIP-FLOPS WITH 3-STATE OUTPUTS**

D2825, JANUARY 1986

- Functionally Equivalent to AMD's AM29821 and AM29822
- Provides Extra Data Width Necessary for Wider Address/Data Paths or Buses with Parity
- Outputs Have Undershoot Protection Circuitry
- Power-Up High-Impedance State
- Package Options Include Both Plastic and Ceramic Carriers in Addition to Plastic and Ceramic DIPs
- Buffered Control Inputs to Reduce DC Loading Effects
- Dependable Texas Instruments Quality and Reliability

description


These 10-bit flip-flops feature three-state outputs designed specifically for driving highly-capacitive or relatively low-impedance loads. They are particularly suitable for implementing wider buffer registers, I/O ports, bidirectional bus drivers with parity, and working registers.

The ten flip-flops are edge-triggered D-type flip-flops. On the positive transition of the clock the Q outputs on the 'ALS29821 will be true, and on the 'ALS29822 will be complementary to the data input.


A buffered output-control (\overline{OC}) input can be used to place the ten outputs in either a normal logic state (high or low levels) or a high-impedance state. In the high-impedance state the outputs neither load nor drive the bus lines significantly. The high-impedance state and increased drive provide the capability to drive the bus lines in a bus-organized system without need for interface or pull-up components. The output control does not affect the internal operation of the flip-flops. Old data can be retained or new data can be entered while the outputs are in the high-impedance state.

The SN54' family is characterized for operation over the full military temperature range of -55°C to 125°C. The SN74' family is characterized for operation from 0°C to 70°C.


SN54ALS29821 . . . JT PACKAGE
SN74ALS29821 . . . DW OR NT PACKAGE




SN54ALS29821 . . . FK PACKAGE
SN74ALS29821 . . . FN PACKAGE



SN54ALS29822 . . . JT PACKAGE
SN74ALS29822 . . . DW OR NT PACKAGE



SN54ALS29822 . . . FK PACKAGE
SN74ALS29822 . . . FN PACKAGE



NC - No internal connection

PRODUCT PREVIEW documents contain information on products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.




SN54ALS29821, SN74ALS29821
10-BIT BUS INTERFACE FLIP-FLOPS WITH 3-STATE OUTPUTS

†ALS29821 FUNCTION TABLE (EACH FLIP-FLOP)


INPUTS			OUTPUT
\overline{OC}	CLK	D	Q
L	↑	H	H
L	↑	L	L
L	L	X	Q_0
H	X	X	Z

†ALS29821 logic symbol†



†This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.
 Pin numbers shown are for DW, JT, and NT packages.

†ALS29821 logic diagram (positive logic)



Pin numbers shown are for DW, JT, and NT packages.

2


ALS and AS Circuits

SN54ALS29822, SN74ALS29822 10-BIT BUS INTERFACE FLIP-FLOPS WITH 3-STATE OUTPUTS

'ALS29822 FUNCTION TABLE (EACH FLIP-FLOP)


INPUTS			OUTPUT
\overline{OC}	CLK	\overline{D}	Q
L	↑	H	L
L	↑	L	H
L	L	X	Q_0
H	X	X	Z

'ALS29822 logic symbol†



†This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.
Pin numbers shown are for DW, JT, and NT packages.

'ALS29822 logic diagram (positive logic)



Pin numbers shown are for DW, JT, and NT packages.

SN54ALS29821, SN54ALS29822, SN74ALS29821, SN74ALS29822

10-BIT BUS INTERFACE FLIP-FLOPS WITH 3-STATE OUTPUTS

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage	5.5 V
Voltage applied to a disabled 3-state output	5.5 V
Input current	100 mA
Output current	-30 mA to 5 mA
Operating free-air temperature range: SN54ALS29821, SN54ALS29822	-55°C to 125°C
SN74ALS29821, SN74ALS29822	0°C to 70°C
Storage temperature range	-65°C to 150°C

recommended operating conditions

		SN54ALS29821			SN74ALS29821			UNIT		
		SN54ALS29822			SN74ALS29822					
		MIN	NOM	MAX	MIN	NOM	MAX			
V_{CC}	Supply voltage	4.5	5	5.5	4.75	5	5.25	V		
V_{IH}	High-level input voltage	2			2			V		
V_{IL}	Low-level input voltage	0.7			0.8			V		
I_{OH}	High-level output current	-15			-24			mA		
I_{OL}	Low-level output current	32			48			mA		
t_w	Pulse duration, CLK high or low							ns		
t_{su}	Setup time, data before CLK [†]							ns		
t_h	Hold time, data after CLK [†]							ns		
T_A	Operating free-air temperature	-55			125			0	70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS [†]	SN54ALS29821			SN74ALS29821			UNIT
		SN54ALS29822			SN74ALS29822			
		MIN	TYP [‡]	MAX	MIN	TYP [‡]	MAX	
V_{IK}	$V_{CC} = \text{MIN}$, $I_I = -18 \text{ mA}$	-1.2			-1.2			V
V_{OH}	$V_{CC} = \text{MIN to MAX}$, $I_{OH} = -0.4 \text{ mA}$	$V_{CC}-2$			$V_{CC}-2$			V
	$V_{CC} = \text{MIN}$, $I_{OH} = -15 \text{ mA}$	2.4	3.3					
	$V_{CC} = \text{MIN}$, $I_{OH} = -24 \text{ mA}$	2.4	3.2					
V_{OL}	$V_{CC} = \text{MIN}$, $I_{OL} = 32 \text{ mA}$	0.25	0.4	0.25	0.4	V		
	$V_{CC} = \text{MIN}$, $I_{OL} = 48 \text{ mA}$			0.35	0.5			
I_{OZH}	$V_{CC} = \text{MAX}$, $V_O = 2.4 \text{ V}$	20			20			μA
I_{OZL}	$V_{CC} = \text{MAX}$, $V_O = 0.4 \text{ V}$	-20			-20			μA
I_I	$V_{CC} = \text{MAX}$, $V_I = 5.5 \text{ V}$	0.1			0.1			mA
I_{IH}	$V_{CC} = \text{MAX}$, $V_I = 2.7 \text{ V}$	20			20			μA
I_{IL}	$V_{CC} = \text{MAX}$, $V_I = 0.4 \text{ V}$	-0.1			-0.1			mA
I_{OS} [§]	$V_{CC} = \text{MAX}$, $V_O = 0 \text{ V}$	-75	-250	-75	-250	mA		
I_{CC}	$V_{CC} = \text{MAX}$	'ALS29821	Outputs high				mA	
			Outputs low					
		Outputs disabled	48	48				
		'ALS29822	Outputs high					
			Outputs low					
		Outputs disabled	48	48				

[†] For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

[‡] All typical values are at $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$.

[§] Not more than one output should be shorted at a time and duration of the short circuit should not exceed one second.

Additional information on these products can be obtained from the factory as it becomes available.

SN54ALS29821, SN54ALS29822, SN74ALS29821, SN74ALS29822
10-BIT BUS INTERFACE FLIP-FLOPS WITH 3-STATE OUTPUTS

switching characteristics

PARAMETER	FROM (INPUT)	TO (OUTPUT)	TEST CONDITIONS See Figure 1	V _{CC} = 5 V, T _A = 25 °C			V _{CC} = MIN TO MAX, [†] T _A = MIN TO MAX [†]				UNIT	
				'ALS29821			SN54ALS29821		SN74ALS29821			
				'ALS29822			SN54ALS29822		SN74ALS29822			
MIN	TYP	MAX	MIN	MAX	MIN	MAX						
t _{PLH}	CLK	Any Q	C _L = 300 pF						ns			
t _{PHL}												
t _{PLH}				6								
t _{PHL}				7								
t _{PZH}	\overline{OC}	Any Q	C _L = 300 pF					ns				
t _{PZL}												
t _{PZH}				12								
t _{PZL}				11								
t _{PHZ}	\overline{OC}	Any Q	C _L = 50 pF					ns				
t _{PLZ}												
t _{PHZ}				5								
t _{PLZ}			C _L = 5 pF		6							


[†] For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

Additional information on these products can be obtained from the factory as it becomes available.

2
ALS and AS Circuits

SN54ALS29821, SN54ALS29822, SN74ALS29821, SN74ALS29822
10-BIT BUS INTERFACE FLIP-FLOPS WITH 3-STATE OUTPUTS





PARAMETER MEASUREMENT INFORMATION



SWITCH POSITION TABLE

TEST	S1	S2
t_{PLH}	Closed	Closed
t_{PHL}	Closed	Closed
t_{PZH}	Open	Closed
t_{PZL}	Closed	Open
t_{PHZ}	Closed	Closed
t_{PLZ}	Closed	Closed

LOAD CIRCUIT



- NOTES: A. C_L includes probe and jig capacitance.
 B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
 C. All input pulses are supplied by generators having the following characteristics: $PRR \leq 10 \text{ MHz}$, $Z_o = 50 \Omega$, $t_r \leq 2.5 \text{ ns}$.

FIGURE 1