

T-41-23  
T-41-25



Description	Part No.	Iv @ 10 mA		2Ø1/2	Fig. No.	Description	Part No.	Iv @ 10 mA		2Ø1/2	Fig. No.	
		Min	Typ					Min	Typ			
<b>Cylindrical and Misc. Lamps</b>												
1.8 mm Round Radial Leads	IRD 1241	0.3	0.7	100	101	5.0 mm Cylindrical 1/2" Leads Flangeless	IRD 0552	0.2	0.4	120	105	
	IHD 1241	0.5	1.6				IHD 0552	0.3	0.5			
	IID 1241	1.3	6.0				IID 0552	0.4	1.0			
	IGD 1241	1.3	5.0				IGD 0552	0.4	1.0			
	IYD 1241	1.3	5.0				IYD 0552	0.4	1.0			
	IED 1241	1.3	5.0				IED 0552	0.4	1.0			
3.0 mm Cylindrical 1" Leads	IRD 0151	0.3	0.4	120	102	5.0 mm Cylindrical 1" Leads	IRD 0571	0.4	0.7	120	106	
	IHD 0151	0.4	0.5				IHD 0571	0.5	1.0			
	IID 0151	0.4	1.0				IID 0571	1.2	3.0			
	IGD 0151	0.4	1.0				IGD 0571	1.2	3.0			
	IYD 0151	0.4	1.0				IYD 0571	1.2	3.0			
3.0 mm Cylindrical 1/2" Leads	IRD 0152	0.2	0.3	150	103	5 mm Super Wide Angle Color Transparent	IRT 0731	0.3	0.5	180	107	
	IHD 0152	0.2	0.3				IHT 0731	0.3	0.6			
	IID 0152	0.3	0.8				IIT 0731	0.6	1.2			
	IGD 0152	0.3	0.8				IGT 0731	0.6	1.2			
	IYD 0152	0.3	0.8				IYT 0731	0.4	1.0			
3 mm Super Wide Angle Super Bright Transparent	ISRC 0741	5.0	10*	124	103	Water Clear	IET 0731	0.6	1.2	180	107	
	IVRT 0741	4.0	7.0*				IRC 0731	0.3	0.5			
	IVGT 0741	3.0	5.5*				IHC 0731	0.3	0.6			
	IVYT 0741	4.0	6.5*				IGC 0731	0.6	1.2			
4.3 mm Right Angle View 1" Leads	IRD 0131	0.2	0.5	64	104	Super Bright Transparent	IYC 0731	0.4	1.0	180	107	
	IHD 0131	0.5	1.0				IEC 0731	0.6	1.2			
	IID 0131	1.0	4.0				ISRC 0731	5.0	10*			
	IGD 0131	1.0	4.0				IVRT 0731	4.0	7.0*			
	IYD 0131	1.0	4.0				IVGT 0731	3.0	5.5*			
IED 0131	1.0	4.0	64	104	Super Bright Transparent	IVYT 0731	4.0	6.5*	180	107		
	1.0	4.0										
<b>Bi-color and Bi-polar Lamps</b>												
T-1, 3 mm Round Bi-Color, 2-Leaded	IHGW 9251	H-	1.0	54	108	2 x 5 mm Bi-Color, 2-Leaded	IHGW 9551	H-	0.6	54	110	
		G-	4.5					G-	1.2			
	IEGW 9251	E-	4.5				IEGW 9551	E-	1.2			
		G-	4.5					G-	1.2			
Bi-Polar Diffused	IIID 9251	1.1	4.5	54	108	Bi-Polar Diffused	IIID 9551	0.8	1.2	54	110	
	IGGD 9251	1.1	4.5				IGGD 9551	0.8	1.2			
	IYYD 9251	1.1	4.5				IYYD 9551	0.6	1.0			
T-1, 3 mm Round Bi-Color, 3-Leaded	IHGW 9253	H-	1.0	54	108	Bi-Color, 3-Leaded	IHGW 9553	H-	0.6	54	110	
		G-	4.5					G-	1.2			
	IEGW 9253	E-	4.5				IEGW 9553	E-	1.2			
G-		4.5	G-	1.2								
5 mm Round Bi-Color, 2-Leaded	IHGW 9451	H-	1.1	54	109	10 mm Round 2 Dice, 2-Leaded (Old Part No. B_50)	II^2D 9651	4.5	15.0	36	111	
		G-	2.5				IG^2D 9651	4.5	15.0			
	IEGW 9451	E-	2.5				IEGW 9661	IY^2D 9651	3.5			13.0
		G-	2.5					G-	9.0			
Bi-Polar Diffused	IIID 9451	0.5	2.5	54	109	10 mm Round Bi-Color, 2-Leaded	IHW 9661	H-	2.0	36	111	
	IGGD 9451	0.5	2.5				IEGW 9661	G-	9.0			
	IYYD 9451	0.5	2.5					E-	9.0			
Bi-Color, 3-Leaded Common Cathode	IHGW 9453	H-	1.1	54	109	Bi-Polar Diffused	IIID 9661	2.5	9.0	36	111	
		G-	2.5				IGGD 9661	2.5	9.0			
	IEGW 9453	E-	2.5				IEGW 9661	IYYD 9661	2.5			9.0
G-		2.5	G-	9.0								
Common Anode	IHGW 9493	H-	1.1	54	109	10 mm Round Bi-Color, 3-Leaded	IHW 9663	H-	2.0	36	111	
		G-	2.5				IEGW 9663	G-	9.0			
	IEGW 9493	E-	2.5					IEGW 9663	E-			9.0
		G-	2.5				G-		9.0			