


Glass Passivated High Efficient Rectifiers

FEATURES

- Superfast recovery time, high voltage
- Low forward voltage, high current capability
- Low thermal resistance
- Low power loss, high efficiency
- UL Recognized File # E-326243
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



TO-247AD (TO-3P)



MECHANICAL DATA

Case: TO-247AD (TO-3P)

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - green compound (halogen-free)

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

Polarity: As marked

Mounting torque: 10 in-lbs maximum

Weight: 5.6 g (approximately)

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted) | | | | | | | | |
|--|--------------------|--------------|-------------|-------------|-------------|-------------|-------------|------|
| PARAMETER | SYMBOL | HER 3001 PT | HER 3002 PT | HER 3003 PT | HER 3004 PT | HER 3005 PT | HER 3006 PT | UNIT |
| Maximum repetitive peak reverse voltage | V _{RRM} | 50 | 100 | 200 | 300 | 400 | 600 | V |
| Maximum RMS voltage | V _{RMS} | 35 | 70 | 140 | 210 | 280 | 420 | V |
| Maximum DC blocking voltage | V _{DC} | 50 | 100 | 200 | 300 | 400 | 600 | V |
| Maximum average forward rectified current | I _{F(AV)} | 30 | | | | | | A |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load | I _{FSM} | 300 | | | | | | A |
| Maximum instantaneous forward voltage (Note 2) I _F =15A | V _F | 1.0 | | | 1.3 | 1.7 | V | |
| Maximum reverse current @ rated VR T _J =25 °C T _J =125 °C | I _R | 10 500 | | | | | | μA |
| Maximum reverse recovery time (Note 2) | t _{rr} | 50 | | | | | 80 | ns |
| Typical junction capacitance (Note 3) | C _j | 175 | | | | | 145 | pF |
| Typical thermal resistance | R _{θJC} | 1.4 | | | | | | °C/W |
| Operating junction temperature range | T _J | - 55 to +150 | | | | | | °C |
| Storage temperature range | T _{STG} | - 55 to +150 | | | | | | °C |

Note 1: 2.0μs Pulse Width, f=1.0KHz

Note 2: Pulse Test : 300μs Pulse Width, 1% Duty Cycle

ORDERING INFORMATION

| PART NO. | PACKING CODE | GREEN COMPOUND CODE | PACKAGE | PACKING |
|--------------------|--------------|---------------------|---------|-----------|
| HER30xxPT (Note 1) | C0 | Suffix "G" | TO-3P | 30 / Tube |

Note 1: "xx" defines voltage from 50V (HER3001PT) to 600V (HER3006PT)

EXAMPLE

| PREFERRED P/N | PART NO. | PACKING CODE | GREEN COMPOUND CODE | DESCRIPTION |
|---------------|-----------|--------------|---------------------|----------------|
| HER3006PT C0 | HER3006PT | C0 | | |
| HER3006PT C0G | HER3006PT | C0 | G | Green compound |

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG. 1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 3- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG. 5- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG. 5 TYPICAL JUNCTION CAPACITANCE PER LEG






FIG.6- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



PACKAGE OUTLINE DIMENSIONS
TO-247AD (TO-3P)



| DIM. | Unit (mm) | | Unit (inch) | |
|------|-----------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 15.90 | 16.40 | 0.626 | 0.646 |
| B | 7.90 | 8.20 | 0.311 | 0.323 |
| C | 5.70 | 6.20 | 0.224 | 0.244 |
| D | 20.80 | 21.30 | 0.819 | 0.839 |
| E | 3.50 | 4.10 | 0.138 | 0.161 |
| F | 19.70 | 20.20 | 0.776 | 0.795 |
| G | - | 4.30 | - | 0.169 |
| H | 2.90 | 3.40 | 0.114 | 0.134 |
| I | 1.93 | 2.18 | 0.076 | 0.086 |
| J | 2.97 | 3.22 | 0.117 | 0.127 |
| K | 1.12 | 1.22 | 0.044 | 0.048 |
| L | 5.20 | 5.70 | 0.205 | 0.224 |
| M | 4.90 | 5.16 | 0.193 | 0.203 |
| N | 2.70 | 3.00 | 0.106 | 0.118 |
| O | 0.51 | 0.76 | 0.020 | 0.030 |

MARKING DIAGRAM



- P/N = Specific Device Code
- G = Green Compound
- YWW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.