



## Kingbright® - Standard - LED's




Case	Type	Colour	Wave Length $\lambda_{peak}$ (nm)	Case-colour	Luminous Intensity ( $I_f = 10 \text{ mA}$ ) $I_v$ (mcd) min. typ.	Full Viewing angle	Dimensions Fig. No.
------	------	--------	--------------------------------------	-------------	---	--------------------	---------------------

	L-53 RD/A	GaAsP	660	red-diffused	0,5 - 1,25	120°	3
	L-53 RD/B				1,25 - 3,2		
	L-53 HD/A	GaP	660	red-diffused	0,8 - 1,25		
	L-53 HD/B				1,25 - 3,2		
	L-53 GD/A	GaP	565	green-diffused	2 - 3,2		
	L-53 GD/B				3,2 - 8		
	L-53 YD/A	GaAsP/GaP	590	yellow-diffused	3,2 - 8		
	L-53 YD/B				8 - 20		
	L-53 ED/A	GaAsP/GaP	625	orange-diffused	3,2 - 8		
	L-53 ED/B				8 - 20		
	L-53 ID/A	GaAsP/GaP	625	red-diffused	3,2 - 8		
	L-53 ID/B				8 - 20		

5 mm

	L-53 IT/A	GaAsP/GaP	625	red-transparent	8 - 20	15°	3
	L-53 IT/B				20 - 80		
	L-53 GT/A	GaP	565	green-transparent	8 - 20		
	L-53 GT/B				20 - 50		
	L-53 YT/A	GaAsP/GaP	590	yellow-transparent	12,5 - 20		
	L-53 YT/B				20 - 80		

5 mm

	L-53 EC/A	GaAsP/GaP	625	water-clear	8 - 20	15°	3
	L-53 EC/B				20 - 80		
	L-53 GC/A	GaP	565	water-clear	8 - 20		
	L-53 GC/B				20 - 50		
	L-53 YC/A	GaAsP/GaP	590	water-clear	12,5 - 20		
	L-53 YC/B				20 - 80		

5 mm