



CIRCUITS	DIM.A	DIM.B	11	25.00	27.50
2	2.50	5.00	12	27.50	30.00
3	5.00	7.50	13	30.00	32.50
4	7.50	10.00	14	32.50	35.00
5	10.00	12.50	15	35.00	37.50
6	12.50	15.00	16	37.50	40.00
7	15.00	17.50	17	40.00	42.50
8	17.50	20.00	18	42.50	45.00
9	20.00	22.50	19	45.00	47.50
10	22.50	25.00	20	47.50	50.00

ELETRICAL:

CURRENT RATING: 3A AC/DC
 VOLTAGE RATING: 250V AC/DC
 CONTACT RESISTANCE: 20 mΩ max.
 WITHSTANDING VOLTAGE: 1000 VAC for 1 min.
 INSULATION RESISTANCE: 1000 MΩ min.
 TEMPERATURE RANGE: -25°C to 85°C

MATERIAL:

CONTACT: Copper Alloy, Tin Plated
 BASE: Nylon 66 UL94V-0

HOW TO ORDER:

W 0 4 5 - X X 1 0 - 0 0 0 - Z

OF POSITIONS:
02 - 20

HOUSING & TERMINATION TYPE:
1 - VERTICAL HEADER THRU HOLE

RoHS COMPLIANT

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	4/19/07

SMP TECHNOLOGY, INC.

SCALE:n/a 2.5mm Pitch, Vertical Header, Disk Drive

TOL. DEC. .X +/- 0.3 .XX +/- 0.2 .XXX +/- 0.1 ANGLE +/- UNIT: mm P/N:W045-XX10-000-Z