


# Dual NPN Digital Transistor

- Pb-Free Package is Available.

## Ordering Information


Device	Marking	Shipping
LUMG3NT1G S-LUMG3NT1G	TR	3000/Tape&Reel
LUMG3NT3G S-LUMG3NT3G	TR	10000/Tape&Reel

**LUMG3NT1G**  
**S-LUMG3NT1G**



## ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25°C)

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V <sub>CEO</sub>	50	Vdc
Collector–Base Voltage	V <sub>CBO</sub>	50	Vdc
Emitter–Base Voltage	V <sub>EBO</sub>	5.0	Vdc
Collector current	I <sub>C</sub>	100	mAdc
Collector power dissipation	P <sub>C</sub>	150	mW
Junction temperature	T <sub>J</sub>	150	°C
Storage Temperature	T <sub>stg</sub>	-55 to +150	°C



## Electrical characteristics (T<sub>a</sub> = 25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV <sub>CBO</sub>	50	–	–	V	I <sub>C</sub> =50μA
Collector-emitter breakdown voltage	BV <sub>CEO</sub>	50	–	–	V	I <sub>C</sub> =1mA
Emitter-base breakdown voltage	BV <sub>EBO</sub>	5	–	–	V	I <sub>E</sub> =50μA
Collector cutoff current	I <sub>CBO</sub>	–	–	0.5	μA	V <sub>CB</sub> =50V
Emitter cutoff current	I <sub>EBO</sub>	–	–	0.5	μA	V <sub>EB</sub> =4V
Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	–	–	0.3	V	I <sub>C</sub> /I <sub>B</sub> =5mA/0.25mA
DC current transfer ratio	h <sub>FE</sub>	100	250	600	–	V <sub>CE</sub> =5V, I <sub>C</sub> =1mA
Transition frequency	f <sub>T</sub>	–	250	–	MHz	V <sub>CE</sub> =10V, I <sub>E</sub> =-5mA, f=100MHz
Input resistance	R <sub>1</sub>	3.29	4.7	6.11	kΩ	–

\* Transition frequency of the transistor

# LUMG3NT1G ;S-LUMG3NT1G

●Electrical characteristic curves




Fig.1 DC current gain vs. collector current





Fig.2 Collector-emitter saturation voltage vs. collector current

# LUMG3NT1G ;S-LUMG3NT1G

## SC-88A



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.071	0.087	1.80	2.20
B	0.045	0.053	1.15	1.35
C	0.031	0.043	0.80	1.10
D	0.004	0.012	0.10	0.30
G	0.026 BSC		0.65 BSC	
H	---	0.004	---	0.10
J	0.004	0.010	0.10	0.25
K	0.004	0.012	0.10	0.30
N	0.008 REF		0.20 REF	
S	0.079	0.087	2.00	2.20

