

$F = 1.27 * (\text{NO of Positions} - 1) \pm 0.15$
 $G = F + 1.27 \pm 0.35$

E=Overall pin length

SPECIFICATIONS
 Contact material: Brass
 Contact plating: Gold flash over nickel
 Insulator material: Nylon 6T

P.C.Board Layout

RoHS compliant


Series	No. of Rows	Type	No. of Pins	Pin Length	Plating
CD3PH	2	ST	XX	CS(A/B/E)	XX
Pin header, DIP type, .40mm square pins	2=Dual rows 1=Single row	ST=Straight RA=Right angle SM=Surface mount	1-40 (single row) 2-80 (double row)	CS=Customer specified pin length. See diagram for A, B and E dimensions	SGXX=Duplex GDXX=Gold XX=Flash if blank, 03, 05, 10, 15, 30µ"

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CD3PH-2-ST-XX-CS(A/B/E)-XX**

Description: Pin header, 1.27x1.27, dual insulator, double row



UNIT: mm