

isc Silicon PNP Power Transistors

BD376/378/380

DESCRIPTION



- DC Current Gain-  
:  $h_{FE} = 20(\text{Min}) @ I_C = -1\text{A}$
- Complement to Type BD375/377/379

APPLICATIONS

- Designed for medium power linear and switching applications

ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )

SYMBOL	PARAMETER	VALUE	UNIT	
$V_{CBO}$	Collector-Base Voltage	BD376	-50	V
		BD378	-75	
		BD380	-100	
$V_{CEO}$	Collector-Emitter Voltage	BD376	-45	V
		BD378	-60	
		BD380	-80	
$V_{EBO}$	Emitter-Base Voltage	-5	V	
$I_C$	Collector Current-Continuous	-2	A	
$I_{CM}$	Collector Current-Peak	-3	A	
$I_B$	Base Current-Continuous	-1	A	
$P_C$	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	25	W	
$T_J$	Junction Temperature	150	$^\circ\text{C}$	
$T_{stg}$	Storage Temperature Range	-55~150	$^\circ\text{C}$	



## isc Silicon PNP Power Transistors

## BD376/378/380

## ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT	
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	BD376	-45			V	
		BD378	-60				
		BD380	-80				
$V_{CBO}$	Collector-Base Voltage	BD376	-50			V	
		BD378	-75				
		BD380	-100				
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = -1\text{A}; I_B = -0.1\text{A}$			-1.0	V	
$V_{BE(on)}$	Base-Emitter On Voltage	$I_C = -1\text{A}; V_{CE} = -2\text{V}$			-1.5	V	
$I_{CBO}$	Collector Cutoff Current	BD376	$V_{CB} = -45\text{V}; I_E = 0$			-2	$\mu\text{A}$
		BD378	$V_{CB} = -60\text{V}; I_E = 0$			-2	
		BD380	$V_{CB} = -80\text{V}; I_E = 0$			-2	
$I_{EBO}$	Emitter Cutoff Current	$V_{EB} = -5\text{V}; I_C = 0$			-0.1	mA	
$h_{FE-1}$	DC Current Gain	$I_C = -0.15\text{A}; V_{CE} = -2\text{V}$	40		375		
$h_{FE-2}$	DC Current Gain	$I_C = -1\text{A}; V_{CE} = -2\text{V}$	20				

## Switching Times

$t_{on}$	Turn-On Time	$I_C = -0.5\text{A}; I_{B1} = -I_{B2} = -50\text{mA}; V_{CC} = -30\text{V}$		0.05		$\mu\text{s}$
$t_{off}$	Turn-Off Time			0.5		$\mu\text{s}$

◆  $h_{FE-1}$  Classifications

6	10	16	25
40-100	63-160	100-250	150-375