



Dual Common Cathode Schottky Rectifier

FEATURES

- Low power loss, high efficiency
- Ideal for automated placement
- Guardring for overvoltage protection
- High surge current capability
- Moisture sensitivity level: level 1, per J-STD-020
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



TO-263AB (D²PAK)



MECHANICAL DATA

Case: TO-263AB (D²PAK)

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - green compound (halogen-free)

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

Polarity: As marked

Weight: 1.37 g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)							
PARAMETER	SYMBOL	MBRS 1045 CT-Y	MBRS 1060 CT-Y	MBRS 10100 CT-Y	MBRS 10150 CT-Y	Unit	
Marking code		MBRS 1045CT	MBRS 1060CT	MBRS 10100CT	MBRS 10150CT		
Maximum repetitive peak reverse voltage	V _{RRM}	45	60	100	150	V	
Maximum RMS voltage	V _{RMS}	31	42	70	105	V	
Maximum DC blocking voltage	V _{DC}	45	60	100	150	V	
Maximum average forward rectified current	I _{F(AV)}	10				A	
Peak repetitive forward current (Rated V _R , Square wave, 20KHz)	I _{FRM}	10				A	
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	120				A	
Peak repetitive reverse surge current (Note 1)	I _R	1				A	
Maximum instantaneous forward voltage (Note 2)	V _F	I _F = 5 A, T _J =25°C	0.70	0.80	0.85	0.88	V
		I _F = 5 A, T _J =125°C	0.57	0.65	0.75	0.78	
		I _F = 10 A, T _J =25°C	0.80	0.90	0.95	0.98	
		I _F = 10 A, T _J =125°C	0.67	0.75	0.85	0.88	
Maximum reverse current @ rated V _R	I _R	T _J =25°C	0.1			mA	
		T _J =100°C	15	10	-		
		T _J =125°C	-	-	5		
Voltage rate of change (Rated V _R)	dV/dt	10000				V/μs	
Typical thermal resistance	R _{θJC}	2				°C/W	
Operating junction temperature range	T _J	- 55 to +150				°C	
Storage temperature range	T _{STG}	- 55 to +150				°C	

Note 1: tp = 2.0 μs, 1.0KHz

Note 2: Pulse test with PW=300μs, 1% duty cycle

ORDERING INFORMATION				
PART NO.	PACKING CODE	PACKING CODE SUFFIX	PACKAGE	PACKING
MBRS10xxCT-Y (Note 1)	RN	G	D ² PAK	800 / 13" Paper reel
	C0		D ² PAK	50 / Tube

Note 1: "xx" defines voltage from 45V (MBRS1045CT-Y) to 150V (MBRS10150CT-Y)

EXAMPLE				
PREFERRED P/N	PART NO.	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
MBRS1060CT-Y RN	MBRS1060CT-Y	RN		
MBRS1060CT-Y RNG	MBRS1060CT-Y	RN	G	Green compound

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG. 3 TYPICAL FORWARD CHARACTERISTICS PER LEG




FIG. 4 TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 5 TYPICAL JUNCTION CAPACITANCE






FIG. 6 TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG




PACKAGE OUTLINE DIMENSIONS
TO-263AB (D²PAK)



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	-	10.5	-	0.413
B	14.60	15.88	0.575	0.625
C	2.41	2.67	0.095	0.105
D	0.68	0.94	0.027	0.037
E	2.29	2.79	0.090	0.110
F	4.44	4.70	0.175	0.185
G	1.14	1.40	0.045	0.055
H	1.14	1.40	0.045	0.055
I	8.25	9.25	0.325	0.364
J	0.36	0.53	0.014	0.021
K	2.03	2.79	0.080	0.110

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	10.8	0.425
B	8.3	0.327
C	1.1	0.043
D	3.5	0.138
E	16.9	0.665
F	9.5	0.374
G	2.5	0.098

MARKING DIAGRAM



P/N = Marking Code
G = Green Compound
YWW = Date Code
F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.