



### SPECIFICATIONS

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 500MΩ Min  
 Withstanding Voltage: 800V AC/minute  
 Pin Material: Brass/Tin-plated  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

### Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2540WR-02P1	2.50	5.00
A2540WR-03P1	5.00	7.50
A2540WR-04P1	7.50	10.00
A2540WR-05P1	10.00	12.50
A2540WR-06P1	12.50	15.00
A2540WR-07P1	15.00	17.50
A2540WR-08P1	17.50	20.00
A2540WR-09P1	20.00	22.50
A2540WR-10P1	22.50	25.00
A2540WR-11P1	25.00	27.50
A2540WR-12P1	27.50	30.00
A2540WR-13P1	30.00	32.50
A2540WR-14P1	32.50	35.00
A2540WR-15P1	35.00	37.50

		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	
		DRAWN BY		APPROVED BY	
		李勤		董正一	
		2005.12.23		2005.12.23	
		GENERAL TOLERANCE			
A2	REVISE	2006.09.18			
A1	REVISE	2006.05.15	X. X±0.25	ANGLE±	
A0	NEW RELEASE	2005.12.23	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
DRAW NO. : A2540WR-XP1					REV. A2

2.50mm PITCH  
90° WAFER