


FAST RECOVERY DIODE

6.6A/100~200V/trr: 30nsec

6VF10CT 6VF20CT
6VF10CTF 6VF20CTF

FEATURES

- TO-251AA Case
- TO-252AA Case, Surface Mount Device
- Ultra - Fast Recovery
- Dual Diodes - Cathode Common
- Low Forward Voltage Drop
- High Surge Capability
- 100 Volts thru 600 Volts Types Available
- Packaged in 16mm Tape and Reel (TO-252AA Case)



Dimensions in mm (Inches)

Approx. Net Weight: 0.3 Grams

0.35 Grams

MAXIMUM RATINGS

Voltage Rating	TYPE	◆6VF10CT ◆6VF10CTF	6VF20CT 6VF20CTF	Unit	
	Symbol				
Repetitive Peak Reverse Voltage	V_{RRM}	100	200	v	
Non-Repetitive Peak Reverse Voltage	V_{RSM}	110	220	v	
Electrical Rating	Symbol	Condition		Rating	Unit
Average Rectified Output Current	I_o	Full rectangular wave conduction	$T_c = 113^\circ C$	6.6	A
		Full sinusoidal wave conduction	$T_c = 117^\circ C$	6.0	
			PCB mounted* $T_a = 28^\circ C$	2.0	
RMS Forward Current	$I_{F(RMS)}$			6.66	A
Peak One-cycle Forward Surge Current	I_{FSM}	50Hz full sine wave, non-repetitive		45	A
Operating Junction Temperature Range	T_{jw}			-40 to 150	$^\circ C$
Storage Temperature Range	T_{stg}			-40 to 150	$^\circ C$

ELECTRICAL & THERMAL CHARACTERISTICS

Characteristics	Symbol	Test Condition	Max.	Unit
Peak Forward Voltage	V_{FM}	$I_{FM} = 3A$ $T_j = 25^\circ C$ per diode leg	0.98	v
Peak Reverse Current	I_{RM}	$V_{RM} = V_{RRM}$ $T_j = 25^\circ C$ per diode leg	10	μA
Reverse Recovery Time	t_{rr}	$I_{FM} = 3A$ $-di/dt = 50A/\mu s$ $T_j = 25^\circ C$	30	ns
Thermal Resistance	$R_{th(j-a)}$	Junction to Ambient, PCB mounted*	80	$^\circ C/W$
	$R_{th(j-c)}$	Junction to Case	5	

* P.C. Board Print Land = 20 x 20mm

◆ For spare parts only

6615123 0002227 703

FIG.1-FORWARD VOLTAGE VS. FORWARD CURRENT




FIG.2-AVERAGE FORWARD POWER DISSIPATION




FIG.3-AVERAGE FORWARD CURRENT VS. AMBIENT TEMPERATURE




FIG.4-AVERAGE FORWARD CURRENT VS. CASE TEMPERATURE




FIG.5-SURGE CURRENT RATINGS

