



SPECIFICATIONS
 Current Rating: 7A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A3961HA-02P	3.96	8.02
A3961HA-03P	7.92	11.98
A3961HA-04P	11.88	15.94
A3961HA-05P	15.84	19.90
A3961HA-06P	19.80	23.86
A3961HA-07P	23.76	27.82
A3961HA-08P	27.72	31.78
A3961HA-09P	31.68	35.74
A3961HA-10P	35.64	39.70
A3961HA-11P	39.60	43.66
A3961HA-12P	43.56	47.62
A3961HA-13P	47.52	51.58
A3961HA-14P	51.48	55.54
A3961HA-15P	55.44	59.50

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	3.96mm PITCH HOUSING
DRAWN BY	APPROVED BY		
董正一	董正一		
2001.02.01	2001.02.01		
GENERAL TOLERANCE			
		X. X±0.25	ANGLE±
		X. XX±0.15	
		X. XXX±0.05	
BO	NEW RELEASE	2006.04.17	DRAW NO. : A3961HA-XP
REV.	DESCRIPTION	DATE	
			REV. B0