

1N4731 and ZM4731 Series 1 W Zener Diodes **1N4731 to 1N4764** (DO-41 Glass Package) $T_A = 25\text{ }^\circ\text{C}$
ZM4731 to ZM4764 (MELF Glass Package) $T_A = 25\text{ }^\circ\text{C}$

Type	Nominal Zener Voltage V_Z at I_{ZT} *	Test Current I_{ZT}	Maximum Zener Impedance			Maximum Reverse Leakage Current		Max. Surge Current 8.3 ms I_{ZS}	Maximum Regulator Current I_{ZM}	
			Z_{ZT} at I_{ZT}	Z_{ZK} at I_{ZK}	I_{ZK}	I_R	at V_R			
	Volts	mA	Ohms	Ohms	mA	μA	Volts	mA	mA	
1N4731	ZM4731	4.3	58	9	400	1.0	50	1	1070	217
1N4732	ZM4732	4.7	53	8	500	1.0	10	1	970	193
1N4733	ZM4733	5.1	49	7	550	1.0	10	1	890	178
1N4734	ZM4734	5.6	45	5	600	1.0	10	2	810	162
1N4735	ZM4735	6.2	41	2	700	1.0	10	3	730	146
1N4736	ZM4736	6.8	37	3.5	700	1.0	10	4	660	133
1N4737	ZM4737	7.5	34	4	700	0.5	10	5	605	121
1N4738	ZM4738	8.2	31	4.5	700	0.5	10	6	550	110
1N4739	ZM4739	9.1	28	5	700	0.5	10	7	500	100
1N4740	ZM4740	10	25	7	700	0.25	10	7.6	454	91
1N4741	ZM4741	11	23	8	700	0.25	5	8.4	414	83
1N4742	ZM4742	12	21	9	700	0.25	5	9.1	380	76
1N4743	ZM4743	13	19	10	700	0.25	5	9.9	344	69
1N4744	ZM4744	15	17	14	700	0.25	5	11.4	304	61
1N4745	ZM4745	16	15.5	16	700	0.25	5	12.2	285	57
1N4746	ZM4746	18	14	20	750	0.25	5	13.7	250	50
1N4747	ZM4747	20	12.5	22	750	0.25	5	15.2	225	45
1N4748	ZM4748	22	11.5	23	750	0.25	5	16.7	205	41
1N4749	ZM4749	24	10.5	25	750	0.25	5	18.2	190	38
1N4750	ZM4750	27	9.5	35	750	0.25	5	20.6	170	34
1N4751	ZM4751	30	8.5	40	1000	0.25	5	22.8	150	30
1N4752	ZM4752	33	7.5	45	1000	0.25	5	25.1	135	27
1N4753	ZM4753	36	7.0	50	1000	0.25	5	27.4	125	25
1N4754	ZM4754	39	6.5	60	1000	0.25	5	29.7	115	23
1N4755	ZM4755	43	6.0	70	1500	0.25	5	32.7	110	22
1N4756	ZM4756	47	5.5	80	1500	0.25	5	35.8	95	19
1N4757	ZM4757	51	5.0	95	1500	0.25	5	38.8	90	18
1N4758	ZM4758	56	4.5	110	2000	0.25	5	42.6	80	16
1N4759	ZM4759	62	4.0	125	2000	0.25	5	47.1	70	14
1N4760	ZM4760	68	3.7	150	2000	0.25	5	51.7	65	13
1N4761	ZM4761	75	3.3	175	2000	0.25	5	56.0	60	12
1N4762	ZM4762	82	3.0	200	3000	0.25	5	62.2	55	11
1N4763	ZM4763	91	2.8	250	3000	0.25	5	69.2	50	10
1N4764	ZM4764	100	2.5	350	3000	0.25	5	76.0	45	9.0

Standard Voltage Tolerance is $\pm 10\%$. Add Suffix "A" for $\pm 5\%$ Tolerance. Other Tolerances, Non-Standard and Higher Zener Voltages Upon Request.

*Measured under thermal equilibrium and DC test conditions.