



SPECIFICATIONS

Current rating: 3 amps
 Contact material: Brass or phosphor bronze
 Contact plating: Gold plate over nickel
 Contact resistance: 20 milliohms max.
 Insulator material: PBT, 30% glass fiber, UL94V-0
 Insulation resistance: 1,000 megohms min.
 Withstanding: 500VAC for 1 min.
 Operating temperature: -55°C to +85°C
 Withdrawal force: 130g-80g min.

| Series | Type | Contact Plating | Color |
|------------------|------------|---|--|
| SHT | 06 | XX | XX |
| 2.54 pitch shunt | 06=Type 06 | TN=Tin GDXX=Gold XX=Gold flash if blank; 15, 30, 50µ" gold | [blank]=Black WT=White BL=Blue YL=Yellow RD=Red GN=Green |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SHT-06-XX-XX**

Description: Shunt, 2.54mm pitch, type 06