



Part No.	Emitting Color + Material	Wave-length (nm)	Lens Type	Iv (mcd) @10mA *20mA		Viewing Angle 2θ1/2	Dimension
				Min.	Max.		

L-1513IT	GaAsP/GaP	625	red transparent	50	200	20°	<p>T-1 3/4 (5mm) Round</p>
L-1513EC	GaAsP/GaP	625	water clear	50	200	20°	
L-1513GT	GaP	565	green transparent	20	150	20°	
L-1513GC	GaP	565	water clear	20	150	20°	
L-1513YT	GaAsP/GaP	590	yellow transparent	20	80	20°	
L-1513YC	GaAsP/GaP	590	water clear	20	80	20°	

L-63ID	GaAsP/GaP	625	red diffused	12.5	50	60°	<p>T-1 3/4 (5mm) Round</p>
L-63IT	GaAsP/GaP	625	red transparent	32	125	30°	
L-63GD	GaP	565	green diffused	5	20	60°	
L-63GT	GaP	565	green transparent	20	80	30°	
L-63YD	GaAsP/GaP	590	yellow diffused	5	20	60°	
L-63YT	GaAsP/GaP	590	yellow transparent	20	80	30°	
L-63SRD	GaAlAs	660	red diffused	*100	*500	60°	
L-63SRT	GaAlAs	660	red transparent	*200	*500	30°	
L-63SRC	GaAlAs	660	water clear	*200	*700	30°	

L-453HD	GaP	700	red diffused	0.8	2	60°	<p>T-1 3/4 (5mm) Round</p>
L-453ID	GaAsP/GaP	625	red diffused	12.5	32	60°	
L-453GD	GaP	565	green diffused	5	20	60°	
L-453YD	GaAsP/GaP	590	yellow diffused	5	20	60°	

L-1593EC	GaAsP/GaP	625	water clear	50	125	30°	<p>T-1 3/4 (5mm) Round</p>
L-1593IT	GaAsP/GaP	625	red transparent	50	125	30°	
L-1593YC	GaAsP/GaP	590	water clear	20	60	30°	
L-1593YT	GaAsP/GaP	590	yellow transparent	20	60	30°	
L-1593SGT	GaP	565	green transparent	*40	*100	30°	
L-1593SRC-D	GaAlAs	660	water clear	*500	*900	30°	
L-1593SRT-D	GaAlAs	660	red transparent	*500	*900	30°	