


## NPN General Purpose Amplifier

## PN2484



TO-92

TO-92

RoHS compliant

### FEATURES:

Designed for low noise, high gain, general purpose amplifier applications at collector currents from 1 $\mu$  to 50 mA.

### ABSOLUTE MAXIMUM RATINGS\* $T_A = 25^\circ\text{C}$ (Unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CEO}$	60	V
Collector-Base Voltage	$V_{CBO}$	60	V
Emitter-Base Voltage	$V_{EBO}$	5	V
Collector Current - Continuous	$I_C$	100	mA
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-55 to +150	$^\circ\text{C}$

\*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

### NOTES:

- 1) These ratings are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

### THERMAL CHARACTERISTICS $T_A = 25^\circ\text{C}$ (Unless otherwise noted)

Parameter	Symbol	Max.	Unit
Total Device Dissipation	$P_D$	625	mW
Derate above 25 $^\circ\text{C}$		5	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Case	$R_{\theta JC}$	83.3	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200	$^\circ\text{C}/\text{W}$



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



**ELECTRICAL CHARACTERISTICS  $T_A = 25^\circ\text{C}$  (Unless otherwise noted)**

Parameter	Symbol	Test Conditions	Min	Max	Units
Collector-Base Breakdown Voltage	$BV_{CBO}$	$I_C = 10 \mu\text{A}, I_B = 0$	60		V
Collector-Emitter Breakdown Voltage*	$BV_{CEO}$	$I_C = 10 \text{mA}, I_E = 0$	60		V
Emitter-Base Breakdown Voltage	$BV_{EBO}$	$I_C = 10 \mu\text{A}, I_E = 0$	6		V
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = 45 \text{V}, I_E = 0$		10	nA
		$V_{CB}=45\text{V}, I_E = 0, T_A=150^\circ\text{C}$		10	$\mu\text{A}$
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = 5.0 \text{V}, I_C = 0$		10	nA
DC Current Gain	$h_{FE}$	$I_C = 1.0 \mu\text{A}, V_{CE} = 5.0 \text{V}$	30		
		$I_C = 10 \mu\text{A}, V_{CE} = 5.0 \text{V}$	100	500	
		$I_C = 100 \mu\text{A}, V_{CE} = 5.0 \text{V}$	175		
		$I_C = 100 \mu\text{A}, V_{CE} = 5.0 \text{V}$ $T_A = -55^\circ\text{C}$	20		
		$I_C = 500 \mu\text{A}, V_{CE} = 5.0 \text{V}$	200		
		$I_C = 1.0 \text{mA}, V_{CE} = 5.0 \text{V}$	250		
		$I_C = 10 \text{mA}, V_{CE} = 5.0 \text{V}^*$		800	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 1.0 \text{mA}, I_B = 0.1 \text{mA}$		0.35	V
Base-Emitter On Voltage	$V_{BE(on)}$	$I_C = 100 \mu\text{A}, V_{CE} = 5.0 \text{V}$	0.5	0.7	V


**SMALL SIGNAL CHARACTERISTICS**

Output Capacitance	$C_{obo}$	$V_{CB} = 5.0 \text{V}, f = 140 \text{kHz}$		6	pF
Input Capacitance	$C_{ibo}$	$V_{EB} = 0.5 \text{V}, f = 140 \text{kHz}$		6	pF

\*Pulse Test: Pulse Width  $\leq 300 \mu\text{s}$ , Duty Cycle  $\leq 3.0\%$

**NOTE: For AEC-Q101 compliant products, please use suffix -AQ in the part number while ordering.**

### Package Details



DIM	MIN	MAX
A	4,32	5,33
B	4,45	5,20
C	3,18	4,19
D	0,41	0,55
E	0,35	0,50
F	5 DEG	
G	1,14	1,40
H	1,20	1,40
K	12,70	—
L	1.982	2.082
M	1,03	1,20

PIN 1 → COLLECTOR  
 PIN 2 → BASE  
 PIN 3 → EMITTER



### Recommended Product Storage Environment for Diode and Transistors

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

#### **Shelf Life of CDIL Products**

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years, the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

#### **Floor Life of CDIL Products and MSL Level**

When the products are opened from the original packing, the floor life will start. For this the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤ 30 °C / 85% RH
2	1 Year	≤ 30 °C / 60% RH
2a	4 Weeks	≤ 30 °C / 60% RH
3	168 Hours	≤ 30 °C / 60% RH
4	72 Hours	≤ 30 °C / 60% RH
5	48 Hours	≤ 30 °C / 60% RH
5a	24 Hours	≤ 30 °C / 60% RH
6	Time on Label(TOL)	≤ 30 °C / 60% RH

Figure 1 Floor Life according to JEDEC MSL Level



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



## Customer Notes

### Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and

## Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of  
Continental Device India Pvt.Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax + 91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. - U32109DL1964PTC004291

PN2482

Rev1\_31012020EM