


**SPECIFICATIONS**

Current Rating: 3A AC,DC  
 Voltage Rating: 300V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 100MΩ Min  
 Withstanding Voltage: 1000V AC/minute  
 Material: Nylon 66,UL94V-0  
 Pantone Color: 153C~154C

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
A2100H-2P	2.00	5.60
A2100H-3P	4.00	7.60
A2100H-4P	6.00	9.60
A2100H-5P	8.00	11.60
A2100H-6P	10.00	13.60
A2100H-7P	12.00	15.60
A2100H-8P	14.00	17.60
A2100H-9P	16.00	19.60
A2100H-10P	18.00	21.60
A2100H-11P	20.00	23.60
A2100H-12P	22.00	25.60
A2100H-13P	24.00	27.60
A2100H-14P	26.00	29.60
A2100H-15P	28.00	31.60

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
UNIT	SCALE	SHEET	TITLE:		
mm		1 of 1	2.00mm PITCH HOUSING		
DRAWN BY	APPROVED BY				
董正一	董正一				
2001.02.01	2001.02.01				
GENERAL TOLERANCE					
		X. X±0.25	ANGLE±		
B0	NEW RELEASE	2006.01.07	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
			DRAW NO. : A2100H-XP		REV. B0