



A=Pos. + 0.2
B=Pos. - 2.0

SPECIFICATIONS

Housing material: PBT, UL94V-1
Pitch: 2.0mm (.079")
Poles: 4~80 (double row)
Accepts terms.: JS-A-2100-G-P
JS-A-2100-T-P

Pos.	Part No.	Dimension		Pos.	Part No.	Dimension	
		A	B			A	B
4	JS-A-2100H-2-04	4.2	2.0	44	JS-A-2100H-2-44	44.2	42.0
6	JS-A-2100H-2-06	6.2	4.0	46	JS-A-2100H-2-46	46.2	44.0
8	JS-A-2100H-2-08	8.2	6.0	48	JS-A-2100H-2-48	48.2	46.0
10	JS-A-2100H-2-10	10.2	8.0	50	JS-A-2100H-2-50	50.2	48.0
12	JS-A-2100H-2-12	12.2	10.0	52	JS-A-2100H-2-52	52.2	50.0
14	JS-A-2100H-2-14	14.2	12.0	54	JS-A-2100H-2-54	54.2	52.0
16	JS-A-2100H-2-16	16.2	14.0	56	JS-A-2100H-2-56	56.2	54.0
18	JS-A-2100H-2-18	18.2	16.0	58	JS-A-2100H-2-58	58.2	56.0
20	JS-A-2100H-2-20	20.2	18.0	60	JS-A-2100H-2-60	60.2	58.0
22	JS-A-2100H-2-22	22.2	20.0	62	JS-A-2100H-2-62	62.2	60.0
24	JS-A-2100H-2-24	24.2	22.0	64	JS-A-2100H-2-64	64.2	62.0
26	JS-A-2100H-2-26	26.2	24.0	66	JS-A-2100H-2-66	66.2	64.0
28	JS-A-2100H-2-28	28.2	26.0	68	JS-A-2100H-2-68	68.2	66.0
30	JS-A-2100H-2-30	30.2	28.0	70	JS-A-2100H-2-70	70.2	68.0
32	JS-A-2100H-2-32	32.2	30.0	72	JS-A-2100H-2-72	72.2	70.0
34	JS-A-2100H-2-34	34.2	32.0	74	JS-A-2100H-2-74	74.2	72.0
36	JS-A-2100H-2-36	36.2	34.0	76	JS-A-2100H-2-76	76.2	74.0
38	JS-A-2100H-2-38	38.2	36.0	78	JS-A-2100H-2-78	78.2	76.0
40	JS-A-2100H-2-40	40.2	38.0	80	JS-A-2100H-2-80	80.2	78.0
42	JS-A-2100H-2-42	42.2	40.0				

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-A-2100H-2-XX**

Description: Mini crimp housing, 2mm pitch