

HIGH EFFICIENCY RECTIFIER

VOLTAGE RANGE 50 to 400 Volts CURRENT 16.0 Amperes

FEATURES


- * Low power loss, high efficiency
- * Low forward voltage drop
- * Low thermal resistance
- * High current capability
- * High speed switching
- * High surge capability
- * High reliability

MECHANICAL DATA

- * Case: D2-PAK molded plastic
- * Epoxy: Device has UL flammability classification 94V-O
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Polarity: As marked

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	HER1601CS	HER1602CS	HER1603CS	HER1604CS	HER1605CS	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	300	400	Volts
Maximum RMS Voltage	VRMS	35	70	140	210	280	Volts
Maximum DC Blocking Voltage	VDC	50	100	200	300	400	Volts
Maximum Average Forward Rectified Current at Tc = 75°C	Io	16.0					Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	IFSM	200					Amps
Typical Current Squared Time	I ² t	167					A ² Sec
Typical Thermal Resistance	RθJC	2.5					°C/W
Typical Junction Capacitance (Note 2)	Cj	40					pF
Operating and Storage Temperature Range	TJ, TSTG	-55 to + 150					°C






ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	HER1601CS	HER1602CS	HER1603CS	HER1604CS	HER1605CS	UNITS
Maximum Instantaneous Forward Voltage at 8.0A DC	Vf	1.0			1.3		Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	Ir	0.5					uAmps
		65					
Maximum Reverse Recovery Time (Note 1)	trr	50					nSec


NOTES : 1. Test Conditions: IF = 0.5A, IR = -1.0A, IRR = -0.25A
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.
3. Suffix "A" = Common Anode.

2022-04
REV:C

RATING AND CHARACTERISTIC CURVES (HER1601CS THRU HER1605CS)



Marking Description



PACKAGING OF DIODE AND BRIDGE RECTIFIERS

TUBE PACK

PACKAGE	PACKING CODE	EA PER BOX	INNER BOX SIZE (mm)	CARTON SIZE (mm)	EA PER CARTON	WEIGHT(Kg)
D2PAK	-C	2,500	340*340*30	360*340*370	25,000	13.43

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.