

zeners

34

TEMPERATURE COMPENSATED ZENERS

CASE SIZE
L

Jedec No.	Solitron Devices Part No.	Normal Zener Voltage (Vz @ Izt) Volts	Maximum Temperature Coefficient \pm %/°C	Zener Test Current (Izt) Ma	Maximum Dynamic Impedance @ (Izt) Ohms
1N4057	TC12.4A50A	12.4	.005	10.0	25
1N4057A	TC12.4A20A	12.4	.002	10.0	25
1N4058	TC14.6A50A	14.6	.005	10.0	30
1N4058A	TC14.6A20A	14.6	.002	10.0	30
1N4059	TC16.8A50A	16.8	.005	10.0	30
1N4059A	TC16.8A20A	16.8	.002	10.0	30
1N4060	TC18.5A50A	18.5	.005	10.0	30
1N4060A	TC18.5A20A	18.5	.002	10.0	30
1N4061	TC21A50A	21.0	.005	10.0	35
1N4061A	TC21A20A	21.0	.002	10.0	35
1N4062	TC23A50A	23.0	.005	10.0	40
1N4062A	TC23A20A	23.0	.002	10.0	40
1N4063	TC27A50A	27.0	.005	10.0	45
1N4063A	TC27A20A	27.0	.002	10.0	45
1N4064	TC30A50A	30.0	.005	10.0	50
1N4064A	TC30A20A	30.0	.002	10.0	50
1N4065	TC33A50A	33.0	.005	10.0	55
1N4065A	TC33A20A	33.0	.002	10.0	55
1N4066	TC37A50A	37.0	.005	7.5	80
1N4066A	TC37A20A	37.0	.002	7.5	80
1N4067	TC43A50A	43.0	.005	7.5	90
1N4067A	TC43A20A	43.0	.002	7.5	90
1N4068	TC47A50A	47.0	.005	7.5	100
1N4068A	TC47A20A	47.0	.002	7.5	100