


# SOT23 NPN SILICON PLANAR SWITCHING TRANSISTORS

ISSUE 2 – SEPTEMBER 94

## FMMT3903 FMMT3904

COMPLIMENTARY TYPES – FMMT3903 - FMMT3905  
FMMT3904 - FMMT3906

PARTMARKING DETAIL – FMMT3903 - 1W  
FMMT3904 - 1A



### ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	$V_{CBO}$	60	V
CollectorEmitter Voltage	$V_{CEO}$	40	V
EmitterBase Voltage	$V_{EBO}$	6	V
Continuous Collector Current	$I_C$	200	mA
Power Dissipation at $T_{amb}=25^{\circ}C$	$P_{tot}$	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

### ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	FMMT3903		FMMT3904		UNIT	CONDITIONS.
		MIN.	MAX.	MIN.	MAX.		
Collector Base Breakdown Voltage	$V_{(BR)CBO}$	60		60		V	$I_C=10\mu A, I_E=0$
CollectorEmitter Breakdown Voltage	$V_{(BR)CEO}$	40		40		V	$I_C=1mA, I_B=0^*$
EmitterBase Breakdown Voltage	$V_{(BR)EBO}$	6		6		V	$I_E=10\mu A, I_C=0$
CollectorEmitter CutOff Current	$I_{CEX}$		50		50	nA	$V_{CE}=30V, V_{BE(off)}=3V$
Base CutOff Current	$I_{BEX}$		50		50	nA	$V_{CE}=30V, V_{EB(off)}=3V$
Static Forward Current Transfer Ratio	$h_{FE}$	20 35 50 30 15	150	40 70 100 60 30	300		$I_C=0.1mA, V_{CE}=1V^*$ $I_C=1mA, V_{CE}=1V^*$ $I_C=10mA, V_{CE}=1V^*$ $I_C=50mA, V_{CE}=1V^*$ $I_C=100mA, V_{CE}=1V^*$
CollectorEmitter Saturation Voltage	$V_{CE(sat)}$		0.2 0.3		0.2 0.3	V	$I_C=10mA, I_B=1mA^*$ $I_C=50mA, I_B=5mA^*$
BaseEmitter Saturation Voltage	$V_{BE(sat)}$	0.65	0.85 0.95	0.65	0.85 0.95	V	$I_C=10mA, I_B=1mA^*$ $I_C=50mA, I_B=5mA^*$
Transition Frequency	$f_T$	250		300		MHz	$I_C=10mA, V_{CE}=20V$ $f=100MHz$
Output Capacitance	$C_{obo}$		4		4	pF	$V_{CB}=5V, I_E=0, f=100KHz$
Input Capacitance	$C_{ibo}$		8		8	pF	$V_{BE}=0.5V, I_C=0, f=100KHz$



# FMMT3903

# FMMT3904

## SWITCHING CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	FMMT3903		FMMT3904		UNIT	CONDITIONS.
		MIN.	MAX.	MIN.	MAX.		
Noise Figure	N		6		5	dB	$V_{CE}=5\text{V}$ $I_C=200\mu\text{A}$ , $R_g=2\text{K}\Omega$ $f=30\text{Hz}$ to $15\text{KHz}$ at -3dB points
Delay Time	$t_d$		35		35	ns	$V_{CC}=3\text{V}$ , $I_C=10\text{mA}$ , $I_{B1}=1\text{mA}$ $V_{BE(off)}=0.5\text{V}$ (See Figure1)
Rise Time	$t_r$		35		35	ns	
Storage Time	$t_s$		175		200	ns	$V_{CC}=3\text{V}$ , $I_C=10\text{mA}$ $I_{B1}=I_{B2}=1\text{mA}$ (See Figure2)
Fall Time	$t_f$		50		50	ns	

\*Measured under pulsed conditions. Pulse width=300 $\mu\text{s}$ . Duty cycle  $\leq 2\%$



# ZETEX

Zetex plc.  
Fields New Road, Chadderton, Oldham, OL9-8NP, United Kingdom.  
Telephone: (44)161 622 4422 (Sales), (44)161 622 4444 (General Enquiries)  
Fax: (44)161 622 4420

Zetex GmbH  
Streitfeldstraße 19  
D-81673 München  
Germany  
Telefon: (49) 89 45 49 49 0  
Fax: (49) 89 45 49 49 9

Zetex Inc.  
47 Mall Drive, Unit 4  
Commack NY 11725  
USA  
Telephone: (631) 543-7100  
Fax: (631) 864-7630

Zetex (Asia) Ltd.  
3701-04 Metroplaza, Tower 1  
Hing Fong Road,  
Kwai Fong, Hong Kong  
Telephone: (852) 26100 611  
Fax: (852) 24250 494

These are supported by  
agents and distributors in  
major countries world-wide  
© Zetex plc 2000

Internet: <http://www.zetex.com>

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.