

PC-Board layout
view component side
thickness 1,6 mm


Coding style table	
	Style A: For connectors 6 poles
	Style B: For connectors from 10 to 14 poles
	Style C: For connectors from 16 to 64 poles

-Technical information available on a separate document ref: DS 09181200001
-Full range of P/N's and dimensions shown on page 2/2

See table for coding
feature arrangement and style

	All Dimensions in mm Original Size DIN A3	Scale 2:1	Free size tol.	Ref.
	All rights reserved Department EC PD - FR	Created by DOUGE	Inspected by BAGDIKIAN	Standardisation HOFFMANN
HARTING Electronics GmbH D-32339 Espelkamp	Title SEK 18 male STD straight W/O lever			Date 2014-05-16
	Type TB	Number 09185XXX924	State Final Release	Doc-Key / ECM-Nr. 100566981/UGD/001/A 50000068837
				Rev. A Page 1/2

Nb of Contacts	Performance Level			Insulator Color	Dimensions			
	PL3	PL2	S4		A Max	C	D	E
06	0918 506 7924	0918 506 6924	0918 506 5924	Grey	27,2	16,76	12,45	2,54 x 2 = 5,08
10	0918 510 7924	0918 510 6924	0918 510 5924		32,3	21,84	17,53	2,54 x 4 = 10,16
14	0918 514 7924	0918 514 6924	0918 514 5924		37,4	26,92	22,61	2,54 x 6 = 15,24
16	0918 516 7924	0918 516 6924	0918 516 5924		39,9	29,46	25,15	2,54 x 7 = 17,78
20	0918 520 7924	0918 520 6924	0918 520 5924		45,0	34,54	30,23	2,54 x 9 = 22,86
24	0918 524 7924	0918 524 6924	0918 524 5924		50,1	39,62	35,91	2,54 x 11 = 27,94
26	0918 526 7924	0918 526 6924	0918 526 5924		52,6	42,16	37,85	2,54 x 12 = 30,48
30	0918 530 7924	0918 530 6924	0918 530 5924		58,0	47,24	43,83	2,54 x 14 = 35,56
34	0918 534 7924	0918 534 6924	0918 534 5924		62,8	52,32	48,01	2,54 x 16 = 40,64
40	0918 540 7924	0918 540 6924	0918 540 5924		70,4	59,94	55,63	2,54 x 19 = 48,26
50	0918 550 7924	0918 550 6924	0918 550 5924		83,1	72,64	68,33	2,54 x 24 = 60,96
60	0918 560 7924	0918 560 6924	0918 560 5924		95,8	85,34	81,03	2,54 x 29 = 73,66
64	0918 564 7924	0918 564 6924	0918 564 5924		100,9	90,42	86,11	2,54 x 31 = 78,74
06	0918 506 7924 001	0918 506 6924 001	0918 506 5924 001		Black	27,2	16,76	12,45
10	0918 510 7924 001	0918 510 6924 001	0918 510 5924 001	32,3		21,84	17,53	2,54 x 4 = 10,16
14	0918 514 7924 001	0918 514 6924 001	0918 514 5924 001	37,4		26,92	22,61	2,54 x 6 = 15,24
16	0918 516 7924 001	0918 516 6924 001	0918 516 5924 001	39,9		29,46	25,15	2,54 x 7 = 17,78
20	0918 520 7924 001	0918 520 6924 001	0918 520 5924 001	45,0		34,54	30,23	2,54 x 9 = 22,86
24	0918 524 7924 001	0918 524 6924 001	0918 524 5924 001	50,1		39,62	35,91	2,54 x 11 = 27,94
26	0918 526 7924 001	0918 526 6924 001	0918 526 5924 001	52,6		42,16	37,85	2,54 x 12 = 30,48
30	0918 530 7924 001	0918 530 6924 001	0918 530 5924 001	58,0		47,24	43,83	2,54 x 14 = 35,56
34	0918 534 7924 001	0918 534 6924 001	0918 534 5924 001	62,8		52,32	48,01	2,54 x 16 = 40,64
40	0918 540 7924 001	0918 540 6924 001	0918 540 5924 001	70,4		59,94	55,63	2,54 x 19 = 48,26
50	0918 550 7924 001	0918 550 6924 001	0918 550 5924 001	83,1		72,64	68,33	2,54 x 24 = 60,96
60	0918 560 7924 001	0918 560 6924 001	0918 560 5924 001	95,8		85,34	81,03	2,54 x 29 = 73,66
64	0918 564 7924 001	0918 564 6924 001	0918 564 5924 001	100,9		90,42	86,11	2,54 x 31 = 78,74

	All rights reserved	Created by	Inspected by	Standardisation	Date	State	
	Department EC PD - FR	DOUGE	BAGDIKIAN	HOFFMANN	2014-05-16	Final Release	
HARTING Electronics GmbH D-32339 Espelkamp		Title SEK 18 male STD straight W/O lever				Doc-Key / ECM-Nr. 100566981/UGD/001/A 50000068837	
		Type	Number		Rev.	Page	
		TB	09185XXX924		A	2/2	