

# Hex 2-input NOR drivers

# 74F805/74F1805

## FEATURES

- High capacitive drive capability
- Choice of configuration  
 Corner V<sub>CC</sub> and GND – 74F805  
 Center V<sub>CC</sub> and GND – 74F1805
- Typical propagation delay of 2.3ns

TYPE	TYPICAL PROPAGATION DELAY	TYPICAL SUPPLY CURRENT ( TOTAL)
74F805	2.3ns	10mA
74F1805	2.3ns	10mA

## ORDERING INFORMATION


DESCRIPTION	ORDER CODE
	COMMERCIAL RANGE V <sub>CC</sub> = 5V ±10%, T <sub>amb</sub> = 0°C to +70°C
20-pin plastic DIP	N74F805N, N74F1805N
20-pin plastic SOL	N74F805D, N74F1805D

## INPUT AND OUTPUT LOADING AND FAN OUT TABLE


PINS	DESCRIPTION	74F (U.L.) HIGH/LOW	LOAD VALUE HIGH/LOW
D <sub>na</sub> – D <sub>nb</sub>	Data inputs	1.0/0.033	20µA/20µA
Q <sub>0</sub> – Q <sub>5</sub>	Data outputs	2400/80	48mA/48mA

NOTE: One (1.0) FAST unit load is defined as: 20µA in the high state and 0.6mA in the low state.


### PIN CONFIGURATION




### LOGIC SYMBOL




### IEC/IEEE SYMBOL




### PIN CONFIGURATION



### LOGIC SYMBOL




### IEC/IEEE SYMBOL



# Hex 2-input NOR drivers

# 74F805/74F1805

## LOGIC DIAGRAM



## FUNCTION TABLE

INPUTS		OUTPUT
Dna	Dnb	$\bar{Q}_n$
H	X	L
X	H	L
L	L	H

- Notes to function table  
 1. H = High voltage level  
 2. L = Low voltage level  
 3. X = Don't care

## ABSOLUTE MAXIMUM RATINGS

(Operation beyond the limit set forth in this table may impair the useful life of the device. Unless otherwise noted these limits are over the operating free air temperature range.)

SYMBOL	PARAMETER	RATING	UNIT
$V_{CC}$	Supply voltage	-0.5 to +7.0	V
$V_{IN}$	Input voltage	-0.5 to +7.0	V
$I_{IN}$	Input current	-30 to +5	mA
$V_{OUT}$	Voltage applied to output in high output state	-0.5 to $V_{CC}$	V
$I_{OUT}$	Current applied to output in low output state	96	mA
$T_{amb}$	Operating free-air temperature range	0 to +70	°C
$T_{stg}$	Storage temperature range	-65 to +150	°C

## RECOMMENDED OPERATING CONDITIONS

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	NOM	MAX	
$V_{CC}$	Supply voltage	4.5	5.0	5.5	V
$V_{IH}$	High-level input voltage	2.0			V
$V_{IL}$	Low-level input voltage			0.8	V
$I_{IK}$	Input clamp current			-18	mA
$I_{OH}$	High-level output current			-48	mA
$I_{OL}$	Low-level output current			48	mA
$T_{amb}$	Operating free air temperature range	0		+70	°C

## Hex 2-input NOR drivers

74F805/74F1805

## DC ELECTRICAL CHARACTERISTICS

(Over recommended operating free-air temperature range unless otherwise noted.)

SYMBOL	PARAMETER	TEST CONDITIONS <sup>1</sup>		LIMITS			UNIT
				MIN	TYP <sup>2</sup>	MAX	
V <sub>OH</sub>	High-level output voltage	V <sub>CC</sub> = MIN, V <sub>IL</sub> = MAX	±10%V <sub>CC</sub>	2.0			V
				V <sub>IH</sub> = MIN, I <sub>OH</sub> = MAX	±5%V <sub>CC</sub>	2.0	
V <sub>OL</sub>	Low-level output voltage	V <sub>CC</sub> = MIN, V <sub>IL</sub> = MAX	±10%V <sub>CC</sub>		0.38	0.55	V
				V <sub>IH</sub> = MIN, I <sub>OI</sub> = MAX	±5%V <sub>CC</sub>	0.38	0.55
V <sub>IK</sub>	Input clamp voltage	V <sub>CC</sub> = MIN, I <sub>I</sub> = I <sub>IK</sub>			-0.73	-1.2	V
I <sub>I</sub>	Input current at maximum input voltage	V <sub>CC</sub> = MAX, V <sub>I</sub> = 7.0V				100	μA
I <sub>IH</sub>	High-level input current	V <sub>CC</sub> = MAX, V <sub>I</sub> = 2.7V				20	μA
I <sub>IL</sub>	Low-level input current	V <sub>CC</sub> = MAX, V <sub>I</sub> = 0.5V				-20	μA
I <sub>O</sub>	Output current <sup>3</sup>	V <sub>CC</sub> = MAX		-60		-150	mA
I <sub>CC</sub>	Supply current (total)	I <sub>CCH</sub>	V <sub>CC</sub> = MAX	V <sub>IN</sub> = GND	3.0	5.0	mA
				V <sub>IN</sub> = 4.5V	17	25	mA

## NOTES:

- For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable type.
- All typical values are at V<sub>CC</sub> = 5V, T<sub>amb</sub> = 25°C.
- The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I<sub>OS</sub>.

## AC ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETER	TEST CONDITION	LIMITS					UNIT
			T <sub>amb</sub> = +25°C			T <sub>amb</sub> = 0°C to +70°C		
			MIN	TYP	MAX	MIN	MAX	
t <sub>PLH</sub> t <sub>PHL</sub>	Propagation delay D <sub>na</sub> , D <sub>nb</sub> to Q <sub>n</sub>	Waveform 1	1.0 1.0	2.0 2.5	4.0 4.5	1.0 1.0	4.0 4.5	ns
t <sub>sk(O)</sub>	Output skew <sup>1,2</sup>	Waveform 2			1.5		1.5	ns


## NOTES:

- [t<sub>PN</sub> actual - t<sub>PM</sub> actual] for any output compared to any other output where N and M are either LH or HL.
- Skew times are valid only under same test conditions (temperature, V<sub>CC</sub>, loading, etc.).

# Hex 2-input NOR drivers

74F805/74F1805

## AC WAVEFORMS



NOTE: For all waveforms,  $V_M = 1.5V$ .

## TEST CIRCUIT AND WAVEFORMS

