

Direct Link

- Cross reference
- RoHS/LF P/N Search
- Customer drawing search
- 3D model search
- Industry Standards

Services

- E-Services
- Distributor list
- Price request
- Order samples

Documentation

- Free search
- Search by category

Start > Search=50006-1090C* > 50006-1090C

50006-1090C

50006-1090C - HPC : Header, Vertical 3 Row 0 Guides, Solder-less Press-Fit, 90 Positions

ACTIVE

Electronics division

Print Datasheet

FCI Brings You More

- Contact our sales/technical support
- Sample request
- Price request
- Check distributor stock

Customer Drawing

[Specifications](#)
[Download document](#)
[Mating Half](#)

General	Dimensional	Mounting	Physical
General			
Configuration	3 Rows with 0 Guide pins		
Contact type	Signal		
Keying Style	Yes		
Product Type	Vertical Header		
Shielded	No		
Number of Lines	90		
Number of power ports	0		
Number of signal pin fields	1		
Dimensional			
Length (Tail)	13.54 mm (0.533 in.)		
Mounting			
Board attachment	Press-Fit		
Physical			
Plating (Contact area)	0.76 µm (30 µin.) Gold 0.76 µm (30 µin.) GXT™ 1.27 µm (50 µin.) Gold		
Plating (Tail)	0.76 µm (30 µin.) GXT™ 0.76 µm (30 µin.) Gold 1.27 µm (50 µin.) Gold		