# 3-917809-2 ACTIVE

### Dynamic Series | Dynamic 5000 Series

TE Internal #: 3-917809-2

Housing, Housing for Male Terminals, Wire-to-Wire, 4 Position, .2 in

[5.08 mm] Centerline, Crimp, 2 Row, Black, Mating Retention,

Dynamic 5000 Series

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings > Receptacle and Tab Housing: 5.08 or 10.16 mm pitch, 250-600V











Connector Product Type: Housing

Connector & Housing Type: Housing for Male Terminals

Connector System: Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 5.08 mm [ .2 in ]

All Receptacle and Tab Housing: 5.08 or 10.16 mm pitch, 250-600V (56)

### **Features**

### **Product Type Features**

Connector & Housing Type  Housing for Male Terminals  Wire-to-Wire	Connector Product Type	Housing
Connector System Wire-to-Wire	Connector & Housing Type	Housing for Male Terminals
	Connector System	Wire-to-Wire
Sealable	Sealable	No
Connector & Contact Terminates To Wire & Cable	Connector & Contact Terminates To	Wire & Cable

### **Configuration Features**

Number of Positions	4
Number of Rows	2

### **Body Features**

	Primary Product Color	Black	
--	-----------------------	-------	--

### **Termination Features**



Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Mating Retention	With
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	5.08 mm[.2 in]
Dimensions	
Row-to-Row Spacing	10.16 mm[.399 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



## Compatible Parts



# Also in the Series | Dynamic 5000 Series







Connector Hardware(3)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(59)



PCB Terminal Blocks(6)



Wire-to-Board Connector Assemblies & Housings(71)



Wire-to-Board Connector Contacts(43)

# Customers Also Bought



















### **Documents**

#### **Product Drawings**

DYNAMIC D-5 TAB HSG D/R 4P X-Y

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_3-917809-2\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-917809-2\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-917809-2\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

1-1773732-4\_DYNAMIC\_SERIES\_CATALOG\_ENGLISH

Japanese

1-1773732-4\_DYNAMIC\_SERIES\_CATALOG\_ENGLISH

English

### **Product Specifications**

**Application Specification** 

English

### **Product Environmental Compliance**

**Product Compliance** 

English

**Product Compliance** 

English

#### **Instruction Sheets**

Instruction Sheet (U.S.)

Housing, Housing for Male Terminals, Wire-to-Wire, 4 Position, .2 in [5.08 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Dynamic 5000 Series



English

Agency Approvals

Agency Approval Document

English