

3 WALL SHROUDED HEADER

Features
 .025 [0.64] square tail in three lengths

Specifications Environmental

Temperature Range:
 -55°C to +120°C

Mechanical

Insulator Material:
 Glass filled polyester, gray, UL94V-0

Contact Material:
 Phosphor Bronze

Contact Plating:
 10µ IN gold

Electrical

Current Rating:
 1 AMP



Dielectric Withstanding Voltage:
 500 Vrms

Insulation Resistance:
 > 1000 Megohms

Mating CA Product:
 IDS2, FID and IDS

Short Latch Ejector
 for use with IDS2 and FID without strain relief

Long Latch Ejector
 for use with IDS2, FID and IDS with strain relief



No. of Positions	Dimensions			Tail Type	Part Numbers		
	A	B	C		no latch	short latch	long latch
* 10	1.26 [32.0]	.700 [17.78]	1.100 [27.94]	Standard	CA-10H3-1B	CA-10H3-1B-S	CA-10H3-1B-SR
				Long	CA-10H3-2B	CA-10H3-2B-S	CA-10H3-2B-SR
10	1.26 [32.0]	.700 [17.78]	1.100 [27.94]	Standard	CA-10H3-1B-SPT	CA-10H3-1B-SPT-S	CA-10H3-1B-SPT-SR
				Long	CA-10H3-2B-SPT	CA-10H3-2B-SPT-S	CA-10H3-2B-SPT-SR
14	1.46 [37.1]	.900 [22.86]	1.300 [33.02]	Standard	CA-14H3-1B	CA-14H3-1B-S	CA-14H3-1B-SR
				Long	CA-14H3-2B	CA-14H3-2B-S	CA-14H3-2B-SR
16	1.56 [39.6]	1.000 [25.40]	1.400 [35.56]	Standard	CA-16H3-1B	CA-16H3-1B-S	CA-16H3-1B-SR
				Long	CA-16H3-2B	CA-16H3-2B-S	CA-16H3-2B-SR
20	1.76 [44.7]	1.200 [30.48]	1.600 [40.64]	Standard	CA-20H3-1B	CA-20H3-1B-S	CA-20H3-1B-SR
				Long	CA-20H3-2B	CA-20H3-2B-S	CA-20H3-2B-SR
26	2.06 [52.3]	1.500 [38.10]	1.900 [48.26]	Standard	CA-26H3-1B	CA-26H3-1B-S	CA-26H3-1B-SR
				Long	CA-26H3-2B	CA-26H3-2B-S	CA-26H3-2B-SR
34	2.46 [62.5]	1.900 [48.26]	2.300 [58.42]	Standard	CA-34H3-1B	CA-34H3-1B-S	CA-34H3-1B-SR
				Long	CA-34H3-2B	CA-34H3-2B-S	CA-34H3-2B-SR
40	2.76 [70.1]	2.200 [55.88]	2.600 [66.04]	Standard	CA-40H3-1B	CA-40H3-1B-S	CA-40H3-1B-SR
				Long	CA-40H3-2B	CA-40H3-2B-S	CA-40H3-2B-SR
50	3.26 [82.8]	2.700 [68.58]	3.100 [78.74]	Standard	CA-50H3-1B	CA-50H3-1B-S	CA-50H3-1B-SR
				Long	CA-50H3-2B	CA-50H3-2B-S	CA-50H3-2B-SR
60	3.76 [95.5]	3.200 [81.28]	3.600 [91.44]	Standard	CA-60H3-1B	CA-60H3-1B-S	CA-60H3-1B-SR
				Long	CA-60H3-2B	CA-60H3-2B-S	CA-60H3-2B-SR

* No Polarizing Slot
 For optional .610 [15.49] long wrap tail: replace -1B with -3WB



E95981



LR65050