



Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 MD165C08D2 MD165C12D2 MD165C16D2 MD165C18D2

165 Amp


Features

- Lead Free Finish/RoHS Compliant (NOTE 1)("P" Suffix designates RoHS Compliant. See ordering information)
- Blocking Voltage:800 to 1800V
- Heat transfer through aluminum oxide DBC ceramic isolated metal baseplate
- · Glass passivated chip


Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

GLASS PASSIVATED RECTIFIER DIODE MODULES 800~1800 Volts



		DIMEN	ISIONS			
DIM	INCHES		MM		NOTE	
	MIN	MAX	MIN	MAX	NOTE	
Α	0.886	0.925	22.50	23.50		
В	1.161	1.201	29.50	30.50		
С	0.335	0.374	8.50	9.50		
D	0.315	0.350	8.00	8.90		
E	1.043	1.083	26.50	27.50		
F	1.122	1.161	28.50	29.50		
G	3.130	3.169	79.50	80.50		
Н	0.492	0.531	12.50	13.50		
1	2.500	2.539	63.50	64.50		
J	3.681	3.720	93.50	94.50		
K	0.256		6.50		Ф	
L	0.492	0.531	12.50	13.50		
М	1.319	1.358	33.50	34.50		





Module Type

TYPE	VRRM	VRSM
MD165C08D2	800V	900V
MD165C12D2	1200V	1300V
MD165C16D2	1600V	1700V
MD165C18D2	1800V	1900V

Maximum Ratings

Symbol	Conditions	Values	Units
IFAV	Single phase ,half wave 180° conduction Tc=101°C	165	Α
IFSM	t=10mS Tvj =45℃	6000	Α
i ² t	t=10mS Tvj =45℃	180000	A^2s
Visol	a.c.50HZ;r.m.s.;1min	3000	V
Tvj		-40 to +150	$^{\circ}\mathbb{C}$
Tstg		-40 to +125	$^{\circ}\mathbb{C}$
Mt	To terminals(M6)	5±15%	Nm
Ms	To heatsink(M6)	5±15%	Nm
Weight	Module (Approximately)	160	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Per diode	0.21	°C/W
Rth(c-s)	Module	0.05	°C/W

Electrical Characteristics

Symbol	Conditions	Values			Unito
		Min.	Тур.	Max.	Units
VFM	T=25℃ IF =300A	_	1.20	1.40	V
Ird	Tvj=150°C VRD=VRRM	_	_	9	mA
r _f	T -25°C		1.25		mΩ
V_{fO}	- T _J =25℃		0.82		V



Performance Curves




Fig1. Power dissipation




Fig3. Transient thermal impedance




Fig5. Forward Characteristics

Micro Commercial Components 250 = bc Α 200 sin.180 rec.120 150 rec 60 100 50 ΙD 0 0 Tc 50 100 °C 150

Fig2.Forward Current Derating Curve




Fig4. Max Non-Repetitive Forward Surge Current



Ordering Information:

Device	Packing
Part Number-BP	Bulk: 8PCS/BOX;80PCS/CTN

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.