


- NOTES:
- ⊕ REPRESENTS A CRITICAL DIMENSION.
 - PUSHOUT FORCE TO BE: 2 lb. (32oz) MIN.
 - ORIENTATION OF PART IN T&R MAY VARY DEPENDING ON POCKET.
 - MAX CUT FLASH .030 ON TAIL AND POST.
 - DUE TO THE HIGH AMOUNT OF INSERTION FORCE NEEDED, THE -LC OPTION IS NOT COMPATIBLE WITH AUTO PLACEMENT. SAMTEC RECOMMENDS MANUAL PLACEMENT FOR ALL ASSEMBLIES WITH THE -LC OPTION.

LEAD STYLE	"B"	TERMINAL	"C"
-01	.230 [5.84]	T-156-08-X-2	.180 [4.57]
-02	.320 [8.13]	T-156-15-X-2	.190 [4.83]
-03	.420 [10.67]	T-156-09-X-2	.190 [4.83]
-04	.120 [3.05]	T-156-07-X-2	.190 [4.83]



TSM-1XX-XX-XXX-SH-XX-XXX-XX

- No. OF POSITIONS**
-02 THRU -36
- LEAD STYLE**
SEE TABLE 1
- PLATING SPEC.**
 -T: TIN
 -S: SELECTIVE GOLD
 -G: GOLD
 -L: SELECTIVE FLASH
 -F: FLASH SELECTIVE
 -H: HEAVY GOLD
 -P: GOLD FLASHED PALLADIUM NICKEL
 -TL: TIN/LEAD (-01 LEAD STYLE ONLY)
 -STL: SELECTIVE TIN/LEAD (-01 LEAD STYLE ONLY)
 -TM: MATTE TIN
 -SM: HEAVY SELECTIVE GOLD, MATTE TIN TAIL
 -LM: LIGHT SELECTIVE GOLD, MATTE TIN TAIL
 -FM: FLASH SELECTIVE GOLD, MATTE TIN TAIL

- OPTION #3**
 -P: PICK & PLACE PAD (SEE FIG. 3)
 USE PPP-08 (-04 THRU -36 POSITION OR 02 & 03 POSITION WITH -TR ONLY)
 -TR: TAPE & REEL (-02 THRU -30 POSITION) (LEADS MAY NOT BE VISIBLE FOR CUSTOMER VISUAL INSPECTION ON SMALLER POSITION PARTS WHEN USED WITH -P OPTION.)
 -K: POLYIMIDE FILM (SEE FIG. 6, SHT. 2) (-04 THRU -36 POSITION) (-02 & -03 POSITIONS WITH -TR ONLY)
- OPTION #2**
 -XXX: POLARIZED POSITION SPECIFY OMITTED PIN

- OPTION #1**
 -LC: LOCKING CLIP (SEE FIG. 1) (SEE NOTE 5)
 USE LC-09-TM (-03 THRU -36 POS USE 2 PER STRIP) (-02 POS USE 1 PER STRIP) (USE TSM-50-SHU)
 -A: ALIGNMENT PIN (USE TSM-XX-SH-A BODY FOR MOLDED -A PINS, POS -02, SEE FIG. 2, SHEET 2) (USE TSM-50-SHU-XX BODY FOR MOLDED -A PINS, POS -03 THRU -50, SEE FIG. 2, SHEET 2) (USE TSM-50-SHU BODY FOR STAKED -A PINS, POS -04 THRU -50, SEE FIG. 4, SHEET 2)
 LEAVE BLANK FOR NO HOLD DOWN OPTION (USE TSM-50-SHU SEE FIG. 1, CAN BE CUT TO POSITION) N/A ON STYLE -03

ROW SPECIFICATION
 -SH: SINGLE HORIZONTAL






FIG. 1
 -LC: LOCKING CLIP OPTION
 CLIPS N/A WITH -A OPTION.



DIFFERENT AS SHOWN. OTHERWISE SAME AS FIG. 1.

TABLE 3

POS.	"E"
ODD	.150 [3.81]
EVEN	.100 [2.54]



FOR ODD: "A" = $\frac{(\text{NO. OF POS} \times .100 [2.54]) - .300 [7.26]}{2}$

FOR EVEN: "A" = $\left[\frac{(\text{NO. OF POS} \times .100 [2.54]) - .300 [7.26]}{2} \right] + .050 [1.27]$

FIG. 3
 -P: PICK & PLACE PAD
 PLACE PPP-08 ON ⊕ AS SHOWN

PROPRIETARY NOTES
 THE DESIGN AND CONSTRUCTION OF THIS PRODUCT ARE THE PROPERTY OF SAMTEC. NO PART OF THIS DOCUMENT IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM SAMTEC.

MATERIAL: BODY: LIQUID CRYSTAL POLYMER COLOR: BLACK TERMINALS: PHOSPHOR BRONZE	<p>samtec</p> <p>EXSPROD/ASSEMBLY/100 TSM5HSM</p> <p>520 PARK EAST BLVD., NEW ALBANY, INDIANA 47150 PHONE (812) 844-8723 P.O. BOX 1147 CODE 55332</p> <p>MADE BY: REIDINGER 7-19-91</p>
---	--

REV. BR

FIG. 2
 -A: ALIGNMENT PIN OPTION (MOLDED)
 DIFFERENT AS SHOWN. OTHERWISE SAME AS FIG. 1.




FIG. 4
 -A: ALIGNMENT PIN OPTION (STAKED)
 DIFFERENT AS SHOWN. OTHERWISE SAME AS FIG. 1.





FIG. 6
 -K POLYIMIDE FILM PAD



NOTE:
 "R" = USED MEASURED DIMENSIONS (REF)
 "S" = $\{("R" - .1969 [5.000]) / 2\} \pm .020 [51]$


PROPRIETARY NOTE
 THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC INC.

DIMENSIONS ARE IN INCHES		UNLESS OTHERWISE NOTED		TOLERANCES ARE:	
ONE PLACE DECIMALS ±.1 [3]	THREE PLACE DECIMALS ±.005 [.13]	ANGLES ± 2°			
TWO PLACE DECIMALS ±.01 [.25]	FOUR PLACE DECIMALS ±.0020 [.051]				

TITLE:
TERMINAL STRIP
SINGLE SURFACE MOUNT

DWG NO:
 TSM-1XX-XX-XXX-SH-XX-XXX-XX
 SHEET 2 OF 2

FIG. 5
 PACKAGING



PT-TSM002-SH-K
 USE TP-24



PT-TSM003-SH-P
 USE TP-24

- 1 ALL PARTS WITH PLASTIC PAD USE PT-TSM003-SH-P
- 2 ALL PARTS WITHOUT PLASTIC PAD USE PT-TSM002-SH-K




FIG. 7
 -SH SURFACEMOUNT DIAGRAM

samtec

EXISPROD ASSEMBLY\100
 TSM SHAM2

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
 PHONE (812) 944-6733 P.O. BOX 1147
 CODE 55322

MADE BY:
 REIDINGER 7-19-91

TSM-1XX-XX-XXX-SH-XX-XXX-XX
 SHEET 2 OF 2