



TS7800

3-Terminal Fixed Positive Voltage Regulators


These voltage regulators are monolithic integrated circuits designed as fixed-voltage regulators for a wide variety of applications including local, on-card regulation. These regulators employ internal current limiting, thermal shutdown, and safe-area compensation.

FEATURES

- Output Current up to 1.5 Ampere
- No External Components Required
- Internal Thermal Overload Protection
- Internal Short-Circuit Current Limiting
- Output Transistor Safe-Area Compensation
- Output Voltage Offered in 2% Tolerance

CIRCUIT SCHEMATIC


Representative Schematic Diagram



With adequate heatsinking they can deliver output currents up to 1.5 ampere.


Although designed primarily as a fixed voltage regulator, these devices can be used with external components to obtain adjustable voltages and currents.

PIN ARRANGEMENT



TYPICAL CONNECTING CIRCUIT

Standard Application



Notes:

A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0V above the output voltage even during the low point on the input ripple voltage.

xx = these two digits of the part number indicate output voltage.

Cin is required if regulator is located an appreciable distance from power supply filter.

Co is not needed for stability, however, it does improve transient response.



TS7800

3-Terminal Fixed Positive Voltage Regulators

- ABSOLUTE MAXIMUM RATINGS** (Ta=25°C)

RATING	SYMBOL	TS7800 Series	UNIT
Input Voltage	Vin *	35	V
Input Voltage	Vin **	40	V
Power Dissipation	Without heatsink	2	
TO-220	Pt ***	15	°C /
TO-220F	With	10	W
TO-252	heatsink	10	
Operating Ambient Temperature	Topr	-20 to +85	°C
Operating Junction Temperature	Tj	0 to +125	°C
Storage Temperature	Tstg	-25 to +150	°C

Note: * TS7805 to TS7818

** TS7824

*** Follow the derating curve

- ORDERING INFORMATION**

DEVICE	OPERATING TEMPERATURE (AMBIENT)	PACKAGE
TS78xxCZ		TO-220
TS78xxCI	-20°C to +85°C	TO-220F
TS78xxCP		TO-252

- TS7805 ELECTRICAL CHARACTERISTICS**

(Vin=10V, Iout=500mA, 0°C≤Tj≤125°C, Cin=0.33 μF, Cout=0.1 μF; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	Vout	Tj=25°C		4.90	5	5.10	V
		7V≤Vin≤20V, 5mA≤Iout≤1.5A, PD≤15W		4.85	-	5.15	V
Line Regulation	REGline	Tj=25°C	7.5V≤Vin≤25V	--	3	100	mV
			8V≤Vin≤12V	--	1	50	mV
Load Regulation	REGload	Tj=25°C	5mA≤Iout≤1.5A	--	15	100	mV
			250mA≤Iout≤750mA	--	5	50	mV
Quiescent Current	Iq	Iout=0, Tj=25°C		--	4.2	8	mA
Quiescent Current Change	Δ Iq	7V≤Vin≤25V		--	--	1.3	mA
		5mA≤Iout≤1.5A		--	--	0.5	mA
Output Noise Voltage	Vn	10Hz≤f≤100KHz, Tj=25°C		--	40	--	μV
Ripple Rejection Ratio	RR	f=120Hz, 8V≤Vin≤18V		62	78	--	dB
Voltage Drop	Vdrop	Iout=1.0A, Tj=25°C		--	2	--	V
Output Resistance	Rout	f=1KHz		--	17	--	mΩ
Output Short Circuit Current	Ios	Tj=25°C		--	750	--	mA
Peak Output Current	Io peak	Tj=25°C		--	2.2	--	A
Temperature Coefficient of Output Voltage	Δ Vout/Δ Tj	Iout=5mA, 0°C≤Tj≤125°C		--	-0.6	--	mV/°C

Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.

This specification applies only for DC power dissipation permitted by absolute maximum ratings.



TS7800

3-Terminal Fixed Positive Voltage Regulators

• TS7806 ELECTRICAL CHARACTERISTICS

($V_{in}=11V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33\mu F$, $C_{out}=0.1\mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		5.88	6	6.12	V
		$8V \leq V_{in} \leq 21V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		5.82	--	6.18	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$8V \leq V_{in} \leq 25V$	--	5	120	mV
			$9V \leq V_{in} \leq 13V$	--	1.5	60	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$5mA \leq I_{out} \leq 1.5A$	--	14	120	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	60	mV
Quiescent Current	I _q	$I_{out}=0$, $T_j=25^{\circ}C$		--	4.3	8	mA
Quiescent Current Change	ΔI_q	$8V \leq V_{in} \leq 25V$		--	--	1.3	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	45	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $9V \leq V_{in} \leq 19V$		59	75	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	R _{out}	$f=1KHz$		--	19	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	550	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-0.7	--	$mV/^{\circ}C$

• TS7808 ELECTRICAL CHARACTERISTICS

($V_{in}=14V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33\mu F$, $C_{out}=0.1\mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		7.84	8	8.16	V
		$10.5V \leq V_{in} \leq 23V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		7.76	--	8.24	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$10.5V \leq V_{in} \leq 25V$	--	6	160	mV
			$11V \leq V_{in} \leq 17V$	--	2	80	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	160	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	80	mV
Quiescent Current	I _q	$I_{out}=0$, $T_j=25^{\circ}C$		--	4.3	8	mA
Quiescent Current Change	ΔI_q	$10.5V \leq V_{in} \leq 25V$		--	--	1	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	52	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $11V \leq V_{in} \leq 21V$		56	72	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	R _{out}	$f=1KHz$		--	16	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	450	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-0.8	--	$mV/^{\circ}C$

Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.

This specification applies only for DC power dissipation permitted by absolute maximum ratings.



TS7800

3-Terminal Fixed Positive Voltage Regulators

• TS7809 ELECTRICAL CHARACTERISTICS

($V_{in}=15V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33 \mu F$, $C_{out}=0.1 \mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		8.82	9	9.18	V
		$11.5V \leq V_{in} \leq 24V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		8.73	--	9.27	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$11.5V \leq V_{in} \leq 26V$	--	6	180	mV
			$11.5V \leq V_{in} \leq 17V$	--	2	90	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$5mA \leq I_{out} \leq 1.5A$	--	12	180	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	90	mV
Quiescent Current	I _q	$I_{out}=0$, $T_j=25^{\circ}C$		--	4.3	8	mA
Quiescent Current Change	ΔI_q	$11.5V \leq V_{in} \leq 26V$		--	--	1	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	52	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $11.5V \leq V_{in} \leq 21.5V$		55	72	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	R _{out}	$f=1KHz$		--	16	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	450	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/^{\circ}C$

• TS7810 ELECTRICAL CHARACTERISTICS

($V_{in}=16V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33 \mu F$, $C_{out}=0.1 \mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		9.8	10	10.2	V
		$12.5V \leq V_{in} \leq 25V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		9.7	-	10.3	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$12.5V \leq V_{in} \leq 28V$	--	7	200	mV
			$13V \leq V_{in} \leq 17V$	--	2	100	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	200	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	100	mV
Quiescent Current	I _q	$I_{out}=0$, $T_j=25^{\circ}C$		--	4.3	8	mA
Quiescent Current Change	ΔI_q	$12.5V \leq V_{in} \leq 28V$		--	--	1	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	70	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $13V \leq V_{in} \leq 23V$		55	71	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	R _{out}	$f=1KHz$		--	18	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	400	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/^{\circ}C$

Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.

This specification applies only for DC power dissipation permitted by absolute maximum ratings.



TS7800

3-Terminal Fixed Positive Voltage Regulators

• TS7812 ELECTRICAL CHARACTERISTICS

($V_{in}=19V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33\mu F$, $C_{out}=0.1\mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		11.76	12.0	12.24	V
		$14.5V \leq V_{in} \leq 27V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		11.64	--	12.36	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$14V \leq V_{in} \leq 30V$	--	10	240	mV
			$15V \leq V_{in} \leq 19V$	--	3	120	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	240	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	120	mV
Quiescent Current	I _q	$T_j=25^{\circ}C$, $I_{out}=0$		--	4.3	8	mA
Quiescent Current Change	ΔI_q	$14.5V \leq V_{in} \leq 30V$		--	--	1	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	75	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $15V \leq V_{in} \leq 25V$		55	71	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	20	--	V
Output Resistance	R _{out}	$f=1KHz$		--	18	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	350	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.2	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/^{\circ}C$

• TS7815 ELECTRICAL CHARACTERISTICS

($V_{in}=23V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33\mu F$, $C_{out}=0.1\mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		14.7	15	15.3	V
		$17.5V \leq V_{in} \leq 30V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		14.55	--	15.45	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$17.5V \leq V_{in} \leq 30V$	--	12	300	mV
			$18V \leq V_{in} \leq 22V$	--	3	150	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	300	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	150	mV
Quiescent Current	I _q	$T_j=25^{\circ}C$, $I_{out}=0$		--	4.3	8	mA
Quiescent Current Change	ΔI_q	$17.5V \leq V_{in} \leq 30V$		--	--	1	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	90	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $18V \leq V_{in} \leq 28V$		54	70	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	R _{out}	$f=1KHz$		--	19	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	230	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.1	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/^{\circ}C$

Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.

This specification applies only for DC power dissipation permitted by absolute maximum ratings.



TS7800

3-Terminal Fixed Positive Voltage Regulators

• TS7818 ELECTRICAL CHARACTERISTICS

($V_{in}=27V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33\mu F$, $C_{out}=0.1\mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		17.64	18	18.36	V
		$21V \leq V_{in} \leq 33V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		17.46	--	18.54	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$21V \leq V_{in} \leq 33V$	--	15	360	mV
			$22V \leq V_{in} \leq 26V$	--	5	180	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	360	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	180	mV
Quiescent Current	I _q	$T_j=25^{\circ}C$, $I_{out}=0$		--	4.5	8	mA
Quiescent Current Change	ΔI_q	$21V \leq V_{in} \leq 33V$		--	--	1	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	110	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $21V \leq V_{in} \leq 31V$		54	70	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	R _{out}	$f=1KHz$		--	22	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	200	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.1	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1	--	$mV/^{\circ}C$

• TS7824 ELECTRICAL CHARACTERISTICS

($V_{in}=33V$, $I_{out}=500mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in}=0.33\mu F$, $C_{out}=0.1\mu F$; unless otherwise specified.)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _{out}	$T_j=25^{\circ}C$		23.52	24	24.48	V
		$26V \leq V_{in} \leq 38V$, $5mA \leq I_{out} \leq 1.5A$, $PD \leq 15W$		23.28	--	24.72	V
Line Regulation	REG _{line}	$T_j=25^{\circ}C$	$26V \leq V_{in} \leq 38V$	--	18	480	mV
			$27V \leq V_{in} \leq 32V$	--	6	240	mV
Load Regulation	REG _{load}	$T_j=25^{\circ}C$	$10mA \leq I_{out} \leq 1.5A$	--	12	480	mV
			$250mA \leq I_{out} \leq 750mA$	--	4	240	mV
Quiescent Current	I _q	$I_{out}=0$, $T_j=25^{\circ}C$		--	4.6	8	mA
Quiescent Current Change	ΔI_q	$26V \leq V_{in} \leq 38V$		--	--	1	mA
		$5mA \leq I_{out} \leq 1.5A$		--	--	0.5	mA
Output Noise Voltage	V _n	$10Hz \leq f \leq 100KHz$, $T_j=25^{\circ}C$		--	170	--	μV
Ripple Rejection Ratio	RR	$f=120Hz$, $26V \leq V_{in} \leq 36V$		54	70	--	dB
Voltage Drop	V _{drop}	$I_{out}=1.0A$, $T_j=25^{\circ}C$		--	2	--	V
Output Resistance	R _{out}	$f=1KHz$		--	28	--	$m\Omega$
Output Short Circuit Current	I _{os}	$T_j=25^{\circ}C$		--	150	--	mA
Peak Output Current	I _{o peak}	$T_j=25^{\circ}C$		--	2.1	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out}/\Delta T_j$	$I_{out}=5mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$		--	-1.5	--	$mV/^{\circ}C$

Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.

This specification applies only for DC power dissipation permitted by absolute maximum ratings.

FIGURE 1 - WORST CASE POWER DISSIPATION versus AMBIENT TEMPERATURE




FIGURE 2 - PEAK OUTPUT CURRENT AS A FUNCTION OF INPUT-OUTPUT DIFFERENTIAL VOLTAGE




FIGURE 3 - QUIESCENT CURRENT AS A FUNCTION OF TEMPERATURE




FIGURE 5 - OUTPUT VOLTAGE AS A FUNCTION OF JUNCTION TEMPERATURE




FIGURE 4 - INPUT OUTPUT DIFFERENTIAL AS A FUNCTION OF JUNCTION TEMPERATURE





FIGURE 6 - OUTPUT IMPEDANCE AS A FUNCTION OF OUTPUT VOLTAGE





TS7800

3-Terminal Fixed Positive Voltage Regulators

FIGURE 7 - RIPPLE REJECTION AS A FUNCTION OF OUTPUT VOLTAGE







FIGURE 8 - RIPPLE REJECTION AS A FUNCTION OF FREQUENCY




TO-220 Mechanical drawing

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.00	10.50	0.394	0.413
B	3.24	4.44	0.128	0.175
C	2.44	2.94	0.096	0.116
D	3.565	4.315	0.140	0.170
E	0.68	0.92	0.027	0.036
F	1.115	1.485	0.044	0.058
G	2.345	2.715	0.092	0.107
H	13.49	14.31	0.531	0.563
I	4.475	5.225	0.176	0.206
J	1.15	1.39	0.045	0.055
K	27.78	29.62	1.094	1.166
L	2.175	2.925	0.086	0.115
M	0.297	0.477	0.012	0.019
N	8.28	8.80	0.326	0.346
O	14.29	15.31	0.563	0.603
P	6.01	6.51	0.237	0.256

TO-220F Mechanical drawing

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.9	10.1	0.390	0.398
B	6.2	6.2	0.244	0.244
C	2.2	2.2	0.087	0.087
D	1.4	1.4	0.055	0.055
E	15.0	15.2	0.591	0.598
F	0.48	0.72	0.019	0.028
G	2.355	2.725	0.093	0.107
H	13.49	14.31	0.531	0.563
I	1.115	1.485	0.044	0.058
J	2.6	2.8	0.102	0.110
K	4.4	4.6	0.173	0.181
L	1.115	1.15	0.045	0.045
M	2.95	3.15	0.116	0.124
N	2.6	2.8	0.102	0.110
O	6.55	6.65	0.258	0.262

TO-252 Mechanical drawing



TO-252 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	6.45	6.55	0.254	0.258
B	9.74	10.7	0.383	0.421
C	0.55	0.65	0.022	0.026
D	2.25	2.35	0.089	0.093
E	1.80	2.80	0.071	0.110
F	0.45	0.56	0.018	0.022
G	0.95	1.45	0.037	0.057
H	0.40	0.60	0.016	0.024
I	5.32	5.57	0.209	0.219
J	1.52	2.03	0.06	0.080