



1 2 3 4 5 6 7 8

A  
B  
C  
D  
E  
F

Performance Level				Dimensions (mm)					
	PL3	PL2	S4						
Nb of Contacts	Part Number	Part Number	Part Number	Insulator Color	A Max	C	D	E	F
06	0919 506 7914	0919 506 6914	0919 506 5914	Beige	27,2	22,86	12,45	2,54 x 2 = 5,08	36,9
10	0919 510 7914	0919 510 6914	0919 510 5914		32,3	27,94	17,53	2,54 x 4 = 10,16	42,0
14	0919 514 7914	0919 514 6914	0919 514 5914		37,4	33,02	22,61	2,54 x 6 = 15,24	47,1
16	0919 516 7914	0919 516 6914	0919 516 5914		39,9	35,56	25,15	2,54 x 7 = 17,78	49,6
20	0919 520 7914	0919 520 6914	0919 520 5914		45,0	40,64	30,23	2,54 x 9 = 22,86	54,7
24	0919 524 7914	0919 524 6914	0919 524 5914		50,1	45,72	35,91	2,54 x 11 = 27,94	59,8
26	0919 526 7914	0919 526 6914	0919 526 5914		52,6	48,26	37,85	2,54 x 12 = 30,48	62,3
30	0919 530 7914	0919 530 6914	0919 530 5914		58,0	53,34	43,83	2,54 x 14 = 35,56	68,2
34	0919 534 7914	0919 534 6914	0919 534 5914		62,8	58,42	48,01	2,54 x 16 = 40,64	72,5
40	0919 540 7914	0919 540 6914	0919 540 5914		70,4	66,04	55,63	2,54 x 19 = 48,26	80,1
50	0919 550 7914	0919 550 6914	0919 550 5914		83,1	78,74	68,33	2,54 x 24 = 60,96	92,8
60	0919 560 7914	0919 560 6914	0919 560 5914		95,8	91,44	81,03	2,54 x 29 = 73,66	105,5
64	0919 564 7914	0919 564 6914	0919 564 5914		100,9	96,52	86,11	2,54 x 31 = 78,74	110,6
06	0919 506 7914 001	0919 506 6914 001	0919 506 5914 001		Black	27,2	22,86	12,45	2,54 x 2 = 5,08
10	0919 510 7914 001	0919 510 6914 001	0919 510 5914 001	32,3		27,94	17,53	2,54 x 4 = 10,16	42,0
14	0919 514 7914 001	0919 514 6914 001	0919 514 5914 001	37,4		33,02	22,61	2,54 x 6 = 15,24	47,1
16	0919 516 7914 001	0919 516 6914 001	0919 516 5914 001	39,9		35,56	25,15	2,54 x 7 = 17,78	49,6
20	0919 520 7914 001	0919 520 6914 001	0919 520 5914 001	45,0		40,64	30,23	2,54 x 9 = 22,86	54,7
24	0919 524 7914 001	0919 524 6914 001	0919 524 5914 001	50,1		45,72	35,91	2,54 x 11 = 27,94	59,8
26	0919 526 7914 001	0919 526 6914 001	0919 526 5914 001	52,6		48,26	37,85	2,54 x 12 = 30,48	62,3
30	0919 530 7914 001	0919 530 6914 001	0919 530 5914 001	58,0		53,34	43,83	2,54 x 14 = 35,56	68,2
34	0919 534 7914 001	0919 534 6914 001	0919 534 5914 001	62,8		58,42	48,01	2,54 x 16 = 40,64	72,5
40	0919 540 7914 001	0919 540 6914 001	0919 540 5914 001	70,4		66,04	55,63	2,54 x 19 = 48,26	80,1
50	0919 550 7914 001	0919 550 6914 001	0919 550 5914 001	83,1		78,74	68,33	2,54 x 24 = 60,96	92,8
60	0919 560 7914 001	0919 560 6914 001	0919 560 5914 001	95,8		91,44	81,03	2,54 x 29 = 73,66	105,5
64	0919 564 7914 001	0919 564 6914 001	0919 564 5914 001	100,9		96,52	86,11	2,54 x 31 = 78,74	110,6

	All rights reserved	Scale 2:1	Free size tol.	Ref.	
	Department EC PD - FR	Created by DOUGE	Inspected by BAGDIKIAN	Standardisation HOFFMANN	Date 2014-05-16
HARTING Electronics GmbH D-32339 Espelkamp		Title SEK 19 male STD straight with short levers			State Final Release
		Type TB	Number 09195XXX914	Doc-Key / ECM-Nr. 100566991/UGD/001/A 50000068837	
					Rev. A
					Page 2/2

1 2 3 4 5 6 7 8

A  
B  
C  
D  
E  
F