



SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 800V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2004HA-2X02P	2.00	4.50
A2004HA-2X03P	4.00	6.50
A2004HA-2X04P	6.00	8.50
A2004HA-2X05P	8.00	10.50
A2004HA-2X06P	10.00	12.50
A2004HA-2X07P	12.00	14.50
A2004HA-2X08P	14.00	16.50
A2004HA-2X09P	16.00	18.50
A2004HA-2X10P	18.00	20.50
A2004HA-2X11P	20.00	22.50
A2004HA-2X12P	22.00	24.50
A2004HA-2X13P	24.00	26.50
A2004HA-2X14P	26.00	28.50
A2004HA-2X15P	28.00	30.50
A2004HA-2X16P	30.00	32.50
A2004HA-2X17P	32.00	34.50
A2004HA-2X18P	34.00	36.50
A2004HA-2X19P	36.00	38.50
A2004HA-2X20P	38.00	40.50

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.			
UNIT	SCALE	SHEET	TITLE:				
mm		1 of 1	2.00mm PITCH HOUSING-LOCK TYPE				
DRAWN BY 歐陽小強 2006.10.27		APPROVED BY 董正一 2006.10.27					
GENERAL TOLERANCE			DRAW NO.: A2004HA-2XNP REV. A1				
A1	REVISE	2007.01.09				X. X±0.25	ANGLE±
A0	NEW RELEASE	2006.10.27				X. XX±0.15	
REV.	DESCRIPTION	DATE	X. XXX±0.05				