



# Quad General Purpose Transistors

PNP Silicon



**MPQ2906**  
**MPQ2907**  
**MPQ2907A\***

\*Motorola Preferred Device



CASE 646-06, STYLE 1  
TO-116

### MAXIMUM RATINGS

Rating	Symbol	MPQ2906 MPQ2907	MPQ2907A	Unit
Collector-Emitter Voltage	$V_{CEO}$	-40	-60	Vdc
Collector-Base Voltage	$V_{CBO}$	-60		Vdc
Emitter-Base Voltage	$V_{EBO}$	-5.0		Vdc
Collector Current — Continuous	$I_C$	-600		mAdc
		Each Transistor	Total Device	
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	0.65 6.5	1.9 19	Watts mW/°C
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-55 to +125		°C

### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	66	°C/W

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

### OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage <sup>(1)</sup> ( $I_C = -10 \text{ mAdc}, I_E = 0$ )	MPQ2906, MPQ2907 MPQ2907A	$V_{(BR)CEO}$	-40 -60	— —	Vdc
Collector-Base Breakdown Voltage ( $I_C = -10 \mu\text{Adc}, I_E = 0$ )		$V_{(BR)CBO}$	-60	—	Vdc
Emitter-Base Breakdown Voltage ( $I_E = -10 \mu\text{Adc}, I_C = 0$ )		$V_{(BR)EBO}$	-5.0	—	Vdc
Collector Cutoff Current ( $V_{CB} = -30 \text{ Vdc}, I_E = 0$ ) ( $V_{CB} = -50 \text{ Vdc}, I_E = 0$ )	MPQ2906, MPQ2907 MPQ2907A	$I_{CBO}$	—	-50	nAdc
Emitter Cutoff Current ( $V_{EB} = -3.0 \text{ Vdc}, I_E = 0$ )	MPQ2906,7 Only	$I_{EBO}$	—	-50	nAdc

1. Pulse Test: Pulse Width  $\leq 300 \mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

Preferred devices are Motorola recommended choices for future use and best overall value.

**MPQ2906 MPQ2907 MPQ2907A**

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Max	Unit
<b>ON CHARACTERISTICS</b>				
DC Current Gain <sup>(1)</sup> ( $I_C = -100 \mu\text{A}$ , $V_{CE} = -10 \text{ Vdc}$ ) ( $I_C = -1.0 \text{ mA}$ , $V_{CE} = -10 \text{ Vdc}$ ) ( $I_C = -10 \text{ mA}$ , $V_{CE} = -10 \text{ Vdc}$ )	MPQ2907A MPQ2907A MPQ2906 MPQ2907	$h_{FE}$	75 100 35 75	— — — —
( $I_C = -10 \text{ mA}$ , $V_{CE} = -10 \text{ Vdc}$ ) ( $I_C = -150 \text{ mA}$ , $V_{CE} = -10 \text{ Vdc}$ ) ( $I_C = -150 \text{ mA}$ , $V_{CE} = -10 \text{ Vdc}$ )	MPQ2907A MPQ2907A MPQ2906 MPQ2907		100 100 40 100	— 300 — —
( $I_C = -300 \text{ mA}$ , $V_{CE} = -10 \text{ Vdc}$ ) ( $I_C = -500 \text{ mA}$ , $V_{CE} = -10 \text{ Vdc}$ )	MPQ2906 MPQ2907 MPQ2906 MPQ2907		20 30 50	— — —
Collector-Emitter Saturation Voltage <sup>(1)</sup> ( $I_C = -150 \text{ mA}$ , $I_B = -15 \text{ mA}$ ) ( $I_C = -300 \text{ mA}$ , $I_B = -30 \text{ mA}$ ) ( $I_C = -500 \text{ mA}$ , $I_B = -50 \text{ mA}$ )	MPQ2906, MPQ2907 MPQ2907A	$V_{CE(sat)}$	— — —	-0.4 -1.6 -1.6
Base-Emitter Saturation Voltage <sup>(1)</sup> ( $I_C = -150 \text{ mA}$ , $I_B = -15 \text{ mA}$ ) ( $I_C = -300 \text{ mA}$ , $I_B = -30 \text{ mA}$ ) ( $I_C = -500 \text{ mA}$ , $I_B = -50 \text{ mA}$ )	MPQ2906, MPQ2907 MPQ2906, MPQ2907 MPQ2907A	$V_{BE(sat)}$	— — —	-1.3 -2.6 -2.6


**SMALL-SIGNAL CHARACTERISTICS**

Current-Gain — Bandwidth Product ( $I_C = -50 \text{ mA}$ , $V_{CE} = -20 \text{ Vdc}$ , $f = 100 \text{ MHz}$ )	$f_T$	200	—	MHz
Output Capacitance ( $V_{CB} = -10 \text{ Vdc}$ , $I_E = 0$ , $f = 1.0 \text{ MHz}$ )	$C_{obo}$	—	8.0	pF
Input Capacitance ( $V_{EB} = 2.0 \text{ Vdc}$ , $I_C = 0$ , $f = 1.0 \text{ MHz}$ )	$C_{ibo}$	—	30	pF


**SWITCHING CHARACTERISTICS**

Turn-On Time ( $V_{CC} = -30 \text{ Vdc}$ , $I_C = -150 \text{ mA}$ , $I_{B1} = 15 \text{ mA}$ )	MPQ2907A Only	$t_{on}$	—	45	ns
Turn-Off Time ( $V_{CC} = -6.0 \text{ Vdc}$ , $I_C = -150 \text{ mA}$ , $I_{B1} = I_{B2} = 15 \text{ mA}$ )	MPQ2907A Only	$t_{off}$	—	180	ns

1. Pulse Test: Pulse Width  $\leq 300 \mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .



**Figure 1. Delay and Rise Time Test Circuit**



**Figure 2. Storage and Fall Time Test Circuit**

6367255 0093241 212




Figure 3. DC Current Gain




Figure 4. "ON" Voltages




Figure 5. Temperature Coefficients

**NOISE FIGURE**  
(VCE = 10 V, TA = 25°C)




Figure 6. Frequency Effects






Figure 7. Source Resistance Effects


**MPQ2906 MPQ2907 MPQ2907A**




**Figure 8. Current-Gain — Bandwidth Product**




**Figure 9. Capacitance**




**Figure 10. Turn-On Time**



**Figure 11. Charge Data**



**Figure 12. Storage Time**



**Figure 13. Fall Time**

6367255 0093243 095




Figure 14. Delay and Rise Time Test Circuit




Figure 15. Storage and Fall Time Test Circuit