

## Voltage regulator diodes

## BZV85 series

## FEATURES


- Total power dissipation: max. 1.3 W
- Tolerance series:  $\pm 5\%$
- Working voltage range: nom. 3.6 to 75 V (E24 range)
- Non-repetitive peak reverse power dissipation: max. 60 W.

## APPLICATIONS

- Stabilization purposes.

## DESCRIPTION

Medium-power voltage regulator diodes in hermetically sealed leaded glass SOD66 (DO-41) packages. The diodes are available in the normalized E24  $\pm 5\%$  tolerance range. The series consists of 33 types with nominal working voltages from 3.6 to 75 V (BZV85-C3V6 to BZV85-C75).



## LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$I_F$	continuous forward current		–	500	mA
$I_{ZSM}$	non-repetitive peak reverse current	$t_p = 100 \mu\text{s}$ ; square wave; $T_j = 25 \text{ }^\circ\text{C}$ prior to surge; see Fig.3	see Table "Per type"		
		$t_p = 10 \text{ ms}$ ; half sinewave; $T_j = 25 \text{ }^\circ\text{C}$ prior to surge	see Table "Per type"		
$P_{tot}$	total power dissipation	$T_{amb} = 25 \text{ }^\circ\text{C}$ ; lead length 10 mm; note 1	–	1.0	W
		note 2	–	1.3	W
$P_{ZSM}$	non-repetitive peak reverse power dissipation	$t_p = 100 \mu\text{s}$ ; square wave; $T_j = 25 \text{ }^\circ\text{C}$ prior to surge	–	60	W
$T_{stg}$	storage temperature		–65	+200	$^\circ\text{C}$
$T_j$	junction temperature		–	200	$^\circ\text{C}$

## Notes

1. Device mounted on a printed circuit-board with 1 cm<sup>2</sup> copper area per lead.
2. If the leads are kept at  $T_{lp} = 55 \text{ }^\circ\text{C}$  at 4 mm from body.

## ELECTRICAL CHARACTERISTICS

## Total series

$T_j = 25 \text{ }^\circ\text{C}$ ; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_F$	forward voltage	$I_F = 50 \text{ mA}$ ; see Fig.4	–	1.0	V

## Voltage regulator diodes

## BZV85 series

Per type

 $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified.

BZV85- CXXX	WORKING VOLTAGE $V_Z$ (V) at $I_{Ztest}$		DIFFERENTIAL RESISTANCE $r_{dif}$ ( $\Omega$ ) at $I_{Ztest}$		TEMP. COEFF. $S_Z$ (mV/K) at $I_{Ztest}$ see Figs 5 and 6		TEST CURRENT $I_{Ztest}$ (mA)	DIODE CAP. $C_d$ (pF) at $f = 1\text{ MHz}$ ; $V_R = 0\text{ V}$	REVERSE CURRENT at REVERSE VOLTAGE		NON-REPETITIVE PEAK REVERSE CURRENT $I_{ZSM}$		
	MIN.	MAX.	MAX.	MIN.	MAX.	$I_R$ ( $\mu\text{A}$ )			$V_R$ (V)	at $t_p = 100\text{ }\mu\text{s}$ ; $T_{amb} = 25\text{ }^\circ\text{C}$		at $t_p = 10\text{ ms}$ ; $T_{amb} = 25\text{ }^\circ\text{C}$	
										MAX. (A)	MAX. (mA)	MAX. (A)	MAX. (mA)
3V6	3.4	3.8	15	-3.5	-1.0	60	MAX.	50	1.0	8.0	2000		
3V9	3.7	4.1	15	-3.5	-1.0	60	MAX.	10	1.0	8.0	1950		
4V3	4.0	4.6	13	-2.7	0	50	MAX.	5	1.0	8.0	1850		
4V7	4.4	5.0	13	-2.0	0.7	45	MAX.	3	1.0	8.0	1800		
5V1	4.8	5.4	10	-0.5	2.2	45	MAX.	3	2.0	8.0	1750		
5V6	5.2	6.0	7	0	2.7	45	MAX.	2	2.0	8.0	1700		
6V2	5.8	6.6	4	0.6	3.6	35	MAX.	2	3.0	7.0	1620		
6V8	6.4	7.2	3.5	1.3	4.3	35	MAX.	2	4.0	7.0	1550		
7V5	7.0	7.9	3	2.5	5.5	35	MAX.	1	4.5	5.0	1500		
8V2	7.7	8.7	5	3.1	6.1	25	MAX.	0.7	5.0	5.0	1400		
9V1	8.5	9.6	5	3.8	7.2	25	MAX.	0.7	6.5	4.0	1340		
10	9.4	10.6	8	4.7	8.5	25	MAX.	0.2	7.0	4.0	1200		
11	10.4	11.6	10	5.3	9.3	20	MAX.	0.2	7.7	3.0	1100		
12	11.4	12.7	10	6.3	10.8	20	MAX.	0.2	8.4	3.0	1000		
13	12.4	14.1	10	7.4	12.0	20	MAX.	0.2	9.1	3.0	900		
15	13.8	15.6	15	8.9	13.6	15	MAX.	0.05	10.5	2.5	760		
16	15.3	17.1	15	10.7	15.4	15	MAX.	0.05	11.0	1.75	700		
18	16.8	19.1	20	11.8	17.1	15	MAX.	0.05	12.5	1.75	600		
20	18.8	21.2	24	13.6	19.1	10	MAX.	0.05	14.0	1.75	540		
22	20.8	23.3	25	16.6	22.1	10	MAX.	0.05	15.5	1.5	500		
24	22.8	25.6	30	18.3	24.3	10	MAX.	0.05	17	1.5	450		
27	25.1	28.9	40	20.1	27.5	8	MAX.	0.05	19	1.2	400		
30	28.0	32.0	45	22.4	32.0	8	MAX.	0.05	21	1.2	380		

## Voltage regulator diodes

## BZV85 series

BZV85- CXXX	WORKING VOLTAGE $V_Z$ (V) at $I_{Ztest}$		DIFFERENTIAL RESISTANCE $r_{diff}$ ( $\Omega$ ) at $I_{Ztest}$	TEMP. COEFF. $S_Z$ (mV/K) at $I_{Ztest}$ see Figs 5 and 6		TEST CURRENT $I_{Ztest}$ (mA)	DIODE CAP. $C_d$ (pF) at $f = 1$ MHz; $V_R = 0$ V	REVERSE CURRENT at REVERSE VOLTAGE		NON-REPETITIVE PEAK REVERSE CURRENT $I_{ZSM}$	
	MIN.	MAX.		MIN.	MAX.			$I_R$ ( $\mu$ A)	$V_R$ (V)	at $t_p = 100 \mu$ s; $T_{amb} = 25^\circ\text{C}$	MAX. (A)
33	31.0	35.0	45	24.8	35.0	8	MAX.	0.05	23	1.0	350
36	34.0	38.0	50	27.2	39.9	8	MAX.	0.05	25	0.9	320
39	37.0	41.0	60	29.6	43.0	6	MAX.	0.05	27	0.8	298
43	40.0	46.0	75	34.0	48.3	6	MAX.	0.05	30	0.7	270
47	44.0	50.0	100	37.4	52.5	4	MAX.	0.05	33	0.6	246
51	48.0	54.0	125	40.8	56.5	4	MAX.	0.05	36	0.5	226
56	52.0	60.0	150	46.8	63.0	4	MAX.	0.05	39	0.4	208
62	58.0	66.0	175	52.2	72.5	4	MAX.	0.05	43	0.4	186
68	64.0	72.0	200	60.5	81.0	4	MAX.	0.05	48	0.35	171
75	70.0	80.0	225	66.5	88.0	4	MAX.	0.05	53	0.3	161

# Voltage regulator diodes

# BZV85 series

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j-tp}$	thermal resistance from junction to tie-point	lead length 4 mm; see Fig.2	110	K/W
$R_{th\ j-a}$	thermal resistance from junction to ambient	lead length 10 mm; note 1	175	K/W

### Note

1. Device mounted on a printed circuit-board with 1 cm<sup>2</sup> copper area per lead.

## GRAPHICAL DATA




Fig.2 Thermal resistance from junction to tie-point with a lead length of 4 mm.

Voltage regulator diodes

BZV85 series

