

GD54/74HC20, GD54/74HCT20

DUAL 4-INPUT NAND GATES


General Description

These devices are identical in pinout to the 54/74LS 20. They contain two independent 4-input NAND gates. These devices are characterized for operation over wide temperature ranges to meet industry and military specifications.

Features

- Low Power consumption characteristic of CMOS devices
- Output drive capability: 10 LS TTL Loads Min.
- Operating speed superior to LS TTL
- Wide operating voltage range: for HC 2 to 6 volts for HCT 4.5 to 5.5 volts
- Low input current: 1 μ A Max.
- Low quiescent current: 20 μ A Max. (74HC)
- High noise immunity characteristic of CMOS
- Diode protection on all inputs

Pin Configuration



Suffix-Blank : Plastic Dual In Line Package
Suffix-J : Ceramic Dual In Line Package
Suffix-D : Small Outline Package

Function Table

		INPUT				OUTPUT
nA	nB	nC	nD	nY		
L	X	X	X			H
X	L	X	X			H
X	X	L	X			H
X	X	X	L			H
H	H	H	H			L

H=HIGH Voltage level

L=LOW Voltage level

X=don't care

Logic Symbol and Diagram




Fig. 1 Logic symbol




Fig. 2 Logic diagram (one gate)

Absolute Maximum Ratings

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CC}	DC Supply voltage		-0.5	+7	V
I_{IK}, I_{OK}	DC input or output diode current	for $V_I < -0.5$ or $V_I > V_{CC} + 0.5V$		20	mA
I_O	DC output source or sink current	for $-0.5V < V_O < V_{CC} + 0.5V$		25	mA
I_{CC}	DC V_{CC} or GND current			50	mA
T_{STG}	Storage temperature range		-65	150	°C
P_D	Power dissipation per package	above $+70^{\circ}\text{C}$: derate linearly with 8mW/K		500	mW
T_L	Lead temperature	At distance $1/16 \pm 1/32$ in. from case for 60 sec(CERAMIC) 10 sec(PLASTIC)		300 260	°C

Recommended Operating Conditions

CHARACTERISTIC	LIMITS		UNITS
	MIN.	MAX.	
Supply-Voltage Range V_{CC} : GD54/74HC Types GD54/74HCT Types	2 4.5	6 5.5	V
DC Input or Output Voltage V_I, V_O	0	V_{CC}	V
Operating Temperature T_A : GD74 Types GD54 Types	-40 -55	+85 +125	°C
Input Rise and Fall times t_r, t_f : GD54/74HC Types at 2V at 4.5V at 6V GD54/74HCT Types at 4.5V		1000 500 400 500	ns

DC Electrical Characteristics for HC

SYMBOL	PARAMETER	TEST CONDITION	V _{CC} (V)	T _A =25°C			GD74HC20		GD54HC20		UNIT
				MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
V _{IH}	HIGH level input Voltage		2.0 4.5 6.0	1.5 3.15 4.2			1.5 3.15 4.2		1.5 3.15 4.2		V
V _{IL}	LOW level input voltage		2.0 4.5 6.0				0.3 0.9 1.2		0.3 0.9 1.2		V
V _{OH}	HIGH level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OH} =-20µA	2.0 4.5 6.0	1.9 4.4 5.9	2.0 4.5 6.0		1.9 4.4 5.9		1.9 4.4 5.9	V
			I _{OH} =-4mA I _{OH} =-5.2mA	4.5 6.0	3.98 5.48	4.3 5.2		3.84 5.34		3.7 5.2	
V _{OL}	LOW level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OL} =20µA	2.0 4.5 6.0			0.1 0.1 0.1		0.1 0.1 0.1		V
			I _{OL} =4mA I _{OL} =5.2mA	4.5 6.0		0.17 0.15	0.26 0.26		0.33 0.33		
I _{IN}	Input leakage Current	V _{IN} =V _{CC} or GND	6.0				0.1		1.0		1.0 µA
I _{CC}	Quiescent Supply Current	V _{IN} =V _{CC} or GND I _{out} =0µA	6.0				2		20		40 µA

DC Electrical Characteristics for HCT

SYMBOL	PARAMETER	TEST CONDITION	V _{CC} (V)	T _A =25°C			GD74HCT20		GD54HCT20		UNIT
				MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
V _{IH}	HIGH level input Voltage		4.5 to 5.5	2.0			2.0		2.0		V
V _{IL}	LOW level input voltage		4.5 to 5.5				0.8		0.8		0.8 V
V _{OH}	HIGH level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OH} =-20µA	4.5	4.4	4.5		4.4		4.4	V
			I _{OH} =-4mA	4.5	3.98	4.3		3.84		3.7	
V _{OL}	LOW level output voltage	V _{IN} =V _{IH} or V _{IL}	I _{OL} =20µA	4.5			0.1		0.1		V
			I _{OL} =4mA	4.5		0.17	0.26		0.33		
I _{IN}	Input leakage Current	V _{IN} =V _{CC} or GND	5.5				0.1		1.0		1.0 µA
I _{CC}	Quiescent Supply Current	V _{IN} =V _{CC} or GND I _{out} =0µA	5.5				2		20		40 µA

AC Characteristics for HC: $t_r=t_f=6\text{ns}$ $C_L=50\text{pF}$

SYMBOL	PARAMETER	V_{CC} (V)	$T_A=25^\circ\text{C}$			GD74HC20		GD54HC20		UNIT
			MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
t_{PLH}/t_{PHL}	Propagation delay time nA, nB, nC, nD to nY	2.0		28	90		110		130	ns
		4.5		10	18		23		26	
		6.0		8	15		20		23	
t_{TLH}/t_{THL}	Output transition time	2.0		25	70		85		100	ns
		4.5		8	15		18		22	
		6.0		7	13		16		19	

AC Characteristics for HCT: $t_r=t_f=6\text{ns}$ $C_L=50\text{pF}$

SYMBOL	PARAMETER	V_{CC} (V)	$T_A=25^\circ\text{C}$			GD74HCT20		GD54HCT20		UNIT
			MIN.	TYP.	MAX.	MIN.	MAX.	MIN.	MAX.	
t_{PLH}/t_{PHL}	Propagation delay time nA, nB, nC, nD to nY	4.5		14	24		30		40	ns
t_{TLH}/t_{THL}	Output transition time	4.5		8	15		18		22	ns

AC Waveform




Fig. 3 Waveforms showing the input (nA, nB, nC, nD) to output (nY) propagation delays and the output transition times.

Note to AC waveform

(1) HC : $V_M = 50\%$, $V_i = \text{GND}$ to V_{CC}
HCT: $V_M = 1.3V$; $V_i = \text{GND}$ to $3V$.