

Am25LS241 • Am54LS/74LS241 Am25LS244 • Am54LS/74LS244

Octal Three-State Buffers

DISTINCTIVE CHARACTERISTICS

- Three-state outputs drive bus lines directly
- Hysteresis at inputs improve noise margin
- PNP inputs reduce D.C. loading on bus lines
- Data-to-output propagation delay times ~ 18ns MAX.
- Enable-to-output ~ 30ns MAX.
- Am25LS241 and 244 specified at 48mA output current
- 20 pin hermetic and molded DIP packages
- 100% product assurance testing to MIL-STD-883 requirements

FUNCTIONAL DESCRIPTION


The 'LS241 and 'LS244 are octal buffers fabricated using advanced low-power Schottky technology. The 20-pin package provides improved printed circuit board density for use in memory address and clock driver applications.

Three-state outputs are provided to drive bus lines directly. The Am25LS241 and Am25LS244 are specified at 48mA and 24mA output sink current, while the Am54LS/74LS241 and Am54LS/74LS244 are guaranteed at 12mA over the military range and 24mA over the commercial range. Four buffers are enabled from one common line and the other four from a second enable line.


The 'LS241 has enable inputs of opposite polarity to allow use as a transceiver without overlap. The 'LS244 enables are of similar polarity for use as a unidirectional buffer in which both halves are enabled simultaneously.

Improved noise rejection and high fan-out are provided by input hysteresis and low current PNP inputs.


LOGIC DIAGRAMS



CONNECTION DIAGRAMS Top Views



LOGIC SYMBOLS



Am25LS241 • Am25LS244

ELECTRICAL CHARACTERISTICS

The Following Conditions Apply Unless Otherwise Specified:

COM'L $T_A = 0^\circ\text{C to } +70^\circ\text{C}$ $V_{CC} = 5.0\text{V} \pm 5\%$ (MIN. = 4.75V MAX. = 5.25V)

MIL $T_A = -55^\circ\text{C to } +125^\circ\text{C}$ $V_{CC} = 5.0\text{V} \pm 10\%$ (MIN. = 4.50V MAX. = 5.50V)

DC CHARACTERISTICS OVER OPERATING RANGE

Parameters	Description		Test Conditions (Note 1)	Min.	Typ. (Note 2)	Max.	Units
V_{OH}	High-Level Output Voltage		$V_{CC} = \text{MIN.}, V_{IH} = 2.0\text{V}$ $I_{OH} = -3.0\text{mA}, V_{IL} = V_{IL}\text{MAX.}$	2.4	3.4		Volts
			$V_{CC} = \text{MIN.},$ $V_{IL} = 0.5\text{V}$	MIL, $I_{OH} = -12\text{mA}$ COM'L, $I_{OH} = -15\text{mA}$	2.0		
V_{OL}	Low-Level Output Voltage		$V_{CC} = \text{MIN.}$	All $I_{OL} = 12\text{mA}$	0.25	0.4	Volts
				All $I_{OL} = 24\text{mA}$	0.35	0.5	
				COM'L, $I_{OL} = 48\text{mA}$		0.55	
V_{IH}	High-Level Input Voltage		Guaranteed input logical HIGH voltage for all inputs	2.0			Volts
V_{IL}	Low-Level Input Voltage	COM'L				0.8	Volts
		MIL				0.7	
V_{IK}	Input Clamp Voltage		$V_{CC} = \text{MIN.}, I_I = -18\text{mA}$			-1.5	Volts
	Hysteresis ($V_{T+} - V_{T-}$)		$V_{CC} = \text{MIN.}$	0.2	0.4		Volts
I_{OZH}	Off-State Output Current, High Level Voltage Applied		$V_{CC} = \text{MAX.}$ $V_{IH} = 2.0\text{V}$ $V_{IL} = V_{IL}\text{MAX.}$	$V_O = 2.7\text{V}$		20	μA
I_{OZL}	Off-State Output Current, Low-Level Voltage Applied				$V_O = 0.4\text{V}$		
I_I	Input Current at Maximum Input Voltage		$V_{CC} = \text{MAX.}, V_I = 7.0\text{V}$			0.1	mA
I_{IH}	High-Level Input Current, Any Input		$V_{CC} = \text{MAX.}, V_{IH} = 2.7\text{V}$			20	μA
I_{IL}	Low-Level Input Current		$V_{CC} = \text{MAX.}, V_{IL} = 0.4\text{V}$			-200	μA
I_{SC}	Short Circuit Output Current (Note 3)		$V_{CC} = \text{MAX.}$	-40		-225	mA
I_{CC}	Supply Current	$V_{CC} = \text{MAX.}$ Outputs open	All Outputs HIGH		13	23	mA
			All Outputs LOW		27	46	
			Outputs at Hi-Z		32	54	

Notes: 1. For conditions shown as MIN. or MAX., use the appropriate value specified under recommended operating conditions.

2. All typical values are $V_{CC} = 5.0\text{V}, T_A = 25^\circ\text{C}$.

3. Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

4

MAXIMUM RATINGS above which the useful life may be impaired

Storage Temperature	-65°C to +150°C
Temperature (Ambient) Under Bias	-55°C to +125°C
Supply Voltage to Ground Potential	-0.5V to +7.0V
DC Voltage Applied to Outputs for HIGH Output State	-0.5V to + V_{CC} max.
DC Input Voltage	-0.5V to +7.0V
DC Output Current	150mA
DC Input Current	-30mA to +5.0mA

Am25LS/54LS/74LS241/244

Am54LS/74LS241 • Am54LS/74LS244

ELECTRICAL CHARACTERISTICS

The Following Conditions Apply Unless Otherwise Specified:

COM'L $T_A = 0^\circ\text{C}$ to $+70^\circ\text{C}$ $V_{CC} = 5.0\text{V} \pm 5\%$ (MIN. = 4.75V MAX. = 5.25V)

MIL $T_A = -55^\circ\text{C}$ to $+125^\circ\text{C}$ $V_{CC} = 5.0\text{V} \pm 10\%$ (MIN. = 4.50V MAX. = 5.50V)


DC CHARACTERISTICS OVER OPERATING RANGE

Parameters	Description	Test Conditions (Note 1)	Min.	Typ. (Note 2)	Max.	Units
V_{OH}	High-Level Output Voltage	$V_{CC} = \text{MIN.}, V_{IH} = 2.0\text{V}$ $I_{OH} = -3.0\text{mA}, V_{IL} = V_{IL\text{MAX.}}$	2.4	3.4		Volts
		$V_{CC} = \text{MIN.},$ $V_{IL} = 0.5\text{V}$	2.0			
		MIL, $I_{OH} = -12\text{mA}$ COM'L, $I_{OH} = -15\text{mA}$	2.0			
V_{OL}	Low-Level Output Voltage	$V_{CC} = \text{MIN.}$		0.25 0.35	0.4 0.5	Volts
V_{IH}	High-Level Input Voltage	Guaranteed input logical HIGH voltage for all inputs	2.0			Volts
V_{IL}	Low-Level Input Voltage	COM'L			0.8	Volts
		MIL			0.7	
V_{IK}	Input Clamp Voltage	$V_{CC} = \text{MIN.}, I_I = -18\text{mA}$			-1.5	Volts
	Hysteresis ($V_{T+} - V_{T-}$)	$V_{CC} = \text{MIN.}$	0.2	0.4		Volts
I_{OZH}	Off-State Output Current, High Level Voltage Applied	$V_{CC} = \text{MAX.}$ $V_{IH} = 2.0\text{V}$ $V_{IL} = V_{IL\text{MAX.}}$	$V_O = 2.7\text{V}$ $V_O = 0.4\text{V}$		20	μA
I_{OZL}	Off-State Output Current, Low-Level Voltage Applied				-20	
I_I	Input Current at Maximum Input Voltage	$V_{CC} = \text{MAX.}, V_I = 7.0\text{V}$			0.1	mA
I_{IH}	High-Level Input Current, Any Input	$V_{CC} = \text{MAX.}, V_{IH} = 2.7\text{V}$			20	μA
I_{IL}	Low-Level Input Current	$V_{CC} = \text{MAX.}, V_{IL} = 0.4\text{V}$			-200	μA
I_{SC}	Short Circuit Output Current (Note 3)	$V_{CC} = \text{MAX.}$	-40		-225	mA
I_{CC}	Supply Current	$V_{CC} = \text{MAX.}$ Outputs open	All Outputs HIGH	13	23	mA
			All Outputs LOW	27	46	
			Outputs at Hi-Z	32	54	

Notes: 1. For conditions shown as MIN. or MAX., use the appropriate value specified under recommended operating conditions.

2. All typical values are $V_{CC} = 5.0\text{V}, T_A = 25^\circ\text{C}$.

3. Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.



SWITCHING CHARACTERISTICS

($T_A = +25^\circ\text{C}$, $V_{CC} = 5.0\text{V}$)

Parameters	Description	Am25LS241 Am25LS244			Am54LS/74LS241 Am54LS/74LS244			Units	Test Conditions (Notes 1-5)
		Min.	Typ.	Max.	Min.	Typ.	Max.		
t_{PLH}	Propagation Delay Time, Low-to-High-Level Output		10	15		12	18	ns	$C_L = 45\text{pF}$ $R_L = 667\Omega$
t_{PHL}	Propagation Delay Time, High-to-Low-Level Output		12	18		12	18	ns	
t_{PZL}	Output Enable Time to Low Level		20	30		20	30	ns	
t_{PZH}	Output Enable Time to High Level		15	23		15	23	ns	$C_L = 5.0\text{pF}$ $R_L = 667\Omega$
t_{PLZ}	Output Disable Time from Low Level		15	25		15	25	ns	
t_{PHZ}	Output Disable Time from High Level		10	18		10	18	ns	


**Am25LS ONLY
SWITCHING CHARACTERISTICS
OVER OPERATING RANGE***

Parameters	Description	Am25LS COM'L		Am25LS MIL		Units	Test Conditions
		Min.	Max.	Min.	Max.		
		$T_A = 0^\circ\text{C to } +70^\circ\text{C}$ $V_{CC} = 5.0\text{V} \pm 5\%$		$T_A = -55^\circ\text{C to } +125^\circ\text{C}$ $V_{CC} = 5.0\text{V} \pm 10\%$			
t_{PLH}	Propagation Delay Time, Low-to-High-Level Output		21		24	ns	$C_L = 45\text{pF}$ $R_L = 667\Omega$
t_{PHL}	Propagation Delay Time, High-to-Low-Level Output		25		28	ns	
t_{PZL}	Output Enable Time to Low Level		41		47	ns	
t_{PZH}	Output Enable Time to High Level		31		47	ns	$C_L = 5.0\text{pF}$ $R_L = 667\Omega$
t_{PLZ}	Output Disable Time from Low Level		34		36	ns	
t_{PHZ}	Output Disable Time from High Level		25		28	ns	

4


*AC performance over the operating temperature range is guaranteed by testing defined in Group A, Subgroup 9.

**LOAD CIRCUIT FOR
THREE-STATE OUTPUTS**



LIC-342

**VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES, THREE-STATE OUTPUTS**



LIC-343

- Notes:
1. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control.
 2. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
 3. In the examples above, the phase relationships between inputs and outputs have been chosen arbitrarily.
 4. Pulse generator characteristics: $PRR \leq 1.0\text{MHz}$, $Z_{OUT} \approx 50\Omega$, $t_r \leq 15\text{ns}$, $t_f \leq 6\text{ns}$.
 5. When measuring t_{PLH} and t_{PHL} , switches S_1 and S_2 are closed.