






## POWER RECTIFIERS, Stud Package, Standard Recovery

ISI Part Number	Maximum Average Rectified Current at $T_c$		Peak Inverse Voltage	Peak Forward Surge Current @ 8.3ms Superimposed	Maximum Peak Forward Voltage at $I_{FSM}$ and $T_c=25^\circ\text{C}$		Maximum Rev. Current @ Rated PIV and $T_c=25^\circ\text{C}$		Maximum Rev. Current @ Rated PIV and $T_c=15^\circ\text{C}$		Outline																																																																																		
	$I_o$ (Amps)	$T_c$ ( $^\circ\text{C}$ )			$V_{FSM}$ (V)	$I_{RM}$ (A)	$I_{RS}$ ( $\mu\text{A}$ )	$I_{RS}$ (mA)	Inches/millimeters																																																																																				
1N1202A 1N1204A 1N1206A 1N3671A 1N3673A	12	150	200	240	1.35	38	5.0	1.0	 <table border="1"> <thead> <tr> <th>Dim</th> <th>Min</th> <th>Max</th> <th>Min</th> <th>Max</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>A</td><td>-</td><td>-</td><td>-</td><td>-</td><td>10-32</td></tr> <tr><td>B</td><td>.424</td><td>.437</td><td>10.77</td><td>11.10</td><td></td></tr> <tr><td>C</td><td>-</td><td>.505</td><td>-</td><td>12.82</td><td></td></tr> <tr><td>D</td><td>.600</td><td>.800</td><td>15.24</td><td>20.32</td><td></td></tr> <tr><td>E</td><td>.422</td><td>.453</td><td>10.72</td><td>11.50</td><td></td></tr> <tr><td>F</td><td>.075</td><td>.175</td><td>1.91</td><td>4.44</td><td></td></tr> <tr><td>G</td><td>-</td><td>.405</td><td>-</td><td>10.29</td><td></td></tr> <tr><td>H</td><td>.163</td><td>.189</td><td>4.15</td><td>4.80</td><td>2</td></tr> <tr><td>J</td><td>-</td><td>.310</td><td>-</td><td>7.87</td><td></td></tr> <tr><td>M</td><td>-</td><td>.350</td><td>-</td><td>8.89</td><td>Dia</td></tr> <tr><td>N</td><td>.020</td><td>.065</td><td>.510</td><td>1.65</td><td></td></tr> <tr><td>P</td><td>.060</td><td>.100</td><td>1.53</td><td>2.54</td><td>Dia</td></tr> </tbody> </table>	Dim	Min	Max	Min	Max	Notes	A	-	-	-	-	10-32	B	.424	.437	10.77	11.10		C	-	.505	-	12.82		D	.600	.800	15.24	20.32		E	.422	.453	10.72	11.50		F	.075	.175	1.91	4.44		G	-	.405	-	10.29		H	.163	.189	4.15	4.80	2	J	-	.310	-	7.87		M	-	.350	-	8.89	Dia	N	.020	.065	.510	1.65		P	.060	.100	1.53	2.54	Dia						
Dim			Min							Max	Min	Max	Notes																																																																																
A			-							-	-	-	10-32																																																																																
B			.424							.437	10.77	11.10																																																																																	
C			-							.505	-	12.82																																																																																	
D			.600							.800	15.24	20.32																																																																																	
E			.422							.453	10.72	11.50																																																																																	
F			.075							.175	1.91	4.44																																																																																	
G			-							.405	-	10.29																																																																																	
H			.163							.189	4.15	4.80	2																																																																																
J	-	.310	-	7.87																																																																																									
M	-	.350	-	8.89	Dia																																																																																								
N	.020	.065	.510	1.65																																																																																									
P	.060	.100	1.53	2.54	Dia																																																																																								
1N1202RA 1N1204RA 1N1206RA 1N3671RA 1N3673RA			200																																																																																										
			400																																																																																										
			600																																																																																										
			800																																																																																										
			1000																																																																																										
			200																																																																																										
			400																																																																																										
			600																																																																																										
			800																																																																																										
			1000																																																																																										
1N1183 1N1184 1N1186 1N1188A 1N1190	35	144	200	500	1.45	110	10	1.0	 <table border="1"> <thead> <tr> <th>Dim</th> <th>Min</th> <th>Max</th> <th>Min</th> <th>Max</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>A</td><td>-</td><td>-</td><td>-</td><td>-</td><td>1/4-28</td></tr> <tr><td>B</td><td>.677</td><td>.687</td><td>17.19</td><td>17.44</td><td></td></tr> <tr><td>C</td><td>-</td><td>.793</td><td>-</td><td>20.14</td><td></td></tr> <tr><td>D</td><td>-</td><td>1.00</td><td>-</td><td>25.40</td><td></td></tr> <tr><td>E</td><td>.427</td><td>.447</td><td>10.84</td><td>11.35</td><td></td></tr> <tr><td>F</td><td>.115</td><td>.200</td><td>2.92</td><td>5.08</td><td></td></tr> <tr><td>G</td><td>-</td><td>.450</td><td>-</td><td>12.95</td><td></td></tr> <tr><td>H</td><td>.220</td><td>.249</td><td>5.59</td><td>6.33</td><td>2</td></tr> <tr><td>J</td><td>-</td><td>.375</td><td>-</td><td>9.52</td><td></td></tr> <tr><td>K</td><td>.156</td><td>-</td><td>3.97</td><td>-</td><td></td></tr> <tr><td>M</td><td>-</td><td>.510</td><td>-</td><td>14.98</td><td>Dia</td></tr> <tr><td>N</td><td>-</td><td>.085</td><td>-</td><td>2.03</td><td></td></tr> <tr><td>P</td><td>.140</td><td>.175</td><td>3.58</td><td>4.44</td><td>Dia</td></tr> </tbody> </table>	Dim	Min	Max	Min	Max	Notes	A	-	-	-	-	1/4-28	B	.677	.687	17.19	17.44		C	-	.793	-	20.14		D	-	1.00	-	25.40		E	.427	.447	10.84	11.35		F	.115	.200	2.92	5.08		G	-	.450	-	12.95		H	.220	.249	5.59	6.33	2	J	-	.375	-	9.52		K	.156	-	3.97	-		M	-	.510	-	14.98	Dia	N	-	.085	-	2.03		P	.140	.175	3.58	4.44	Dia
Dim			Min							Max	Min	Max	Notes																																																																																
A			-							-	-	-	1/4-28																																																																																
B			.677							.687	17.19	17.44																																																																																	
C			-							.793	-	20.14																																																																																	
D	-	1.00	-	25.40																																																																																									
E	.427	.447	10.84	11.35																																																																																									
F	.115	.200	2.92	5.08																																																																																									
G	-	.450	-	12.95																																																																																									
H	.220	.249	5.59	6.33	2																																																																																								
J	-	.375	-	9.52																																																																																									
K	.156	-	3.97	-																																																																																									
M	-	.510	-	14.98	Dia																																																																																								
N	-	.085	-	2.03																																																																																									
P	.140	.175	3.58	4.44	Dia																																																																																								
1N1183A 1N1185A 1N1186A 1N1188A 1N1190A	40	144	200	800	1.19	90	40	2.0	 <table border="1"> <thead> <tr> <th>Dim</th> <th>Min</th> <th>Max</th> <th>Min</th> <th>Max</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>A</td><td>-</td><td>-</td><td>-</td><td>-</td><td>1/4-28</td></tr> <tr><td>B</td><td>.677</td><td>.687</td><td>17.19</td><td>17.44</td><td></td></tr> <tr><td>C</td><td>-</td><td>.793</td><td>-</td><td>20.14</td><td></td></tr> <tr><td>D</td><td>-</td><td>1.00</td><td>-</td><td>25.40</td><td></td></tr> <tr><td>E</td><td>.427</td><td>.447</td><td>10.84</td><td>11.35</td><td></td></tr> <tr><td>F</td><td>.115</td><td>.200</td><td>2.92</td><td>5.08</td><td></td></tr> <tr><td>G</td><td>-</td><td>.450</td><td>-</td><td>12.95</td><td></td></tr> <tr><td>H</td><td>.220</td><td>.249</td><td>5.59</td><td>6.33</td><td>2</td></tr> <tr><td>J</td><td>-</td><td>.375</td><td>-</td><td>9.52</td><td></td></tr> <tr><td>K</td><td>.156</td><td>-</td><td>3.97</td><td>-</td><td></td></tr> <tr><td>M</td><td>-</td><td>.510</td><td>-</td><td>14.98</td><td>Dia</td></tr> <tr><td>N</td><td>-</td><td>.085</td><td>-</td><td>2.03</td><td></td></tr> <tr><td>P</td><td>.140</td><td>.175</td><td>3.58</td><td>4.44</td><td>Dia</td></tr> </tbody> </table>	Dim	Min	Max	Min	Max	Notes	A	-	-	-	-	1/4-28	B	.677	.687	17.19	17.44		C	-	.793	-	20.14		D	-	1.00	-	25.40		E	.427	.447	10.84	11.35		F	.115	.200	2.92	5.08		G	-	.450	-	12.95		H	.220	.249	5.59	6.33	2	J	-	.375	-	9.52		K	.156	-	3.97	-		M	-	.510	-	14.98	Dia	N	-	.085	-	2.03		P	.140	.175	3.58	4.44	Dia
Dim			Min							Max	Min	Max	Notes																																																																																
A			-							-	-	-	1/4-28																																																																																
B			.677							.687	17.19	17.44																																																																																	
C			-							.793	-	20.14																																																																																	
D	-	1.00	-	25.40																																																																																									
E	.427	.447	10.84	11.35																																																																																									
F	.115	.200	2.92	5.08																																																																																									
G	-	.450	-	12.95																																																																																									
H	.220	.249	5.59	6.33	2																																																																																								
J	-	.375	-	9.52																																																																																									
K	.156	-	3.97	-																																																																																									
M	-	.510	-	14.98	Dia																																																																																								
N	-	.085	-	2.03																																																																																									
P	.140	.175	3.58	4.44	Dia																																																																																								
			400																																																																																										
			600																																																																																										
			800																																																																																										
			1000																																																																																										

## AUTOMOTIVE RECTIFIER DIODES, Plastic Button Package

ISI Part Number	Maximum Average Rectified Current at $T_c$		Peak Inverse Voltage	Peak Forward Surge Current @ 8.3ms Superimposed	Maximum Fwd Voltage @ Rated $I_o$ and $T_c=25^\circ\text{C}$	Maximum Reverse Current at Rated PIV		Reverse Recovery Time at Rated PIV	Outline															
	$I_o$ (Amps)	$T_c$ ( $^\circ\text{C}$ )				$I_{RS}$ ( $\mu\text{A}$ )	$I_{RS}$ (mA)																	
RA2505 RA251 RA252 RA254 RA256 RA258 RA2510	25	150	50	300	1.0	5.0	25	300																
RA3505 RA351 RA352 RA354 RA356 RA358 RA3510			35							150	50	400	1.0	5.0	25	300								
																			100					
																			200					
																			400					
																			600					
																			800					
				1000																				