



Dimensions		
Poles	A	B
2	.256	.098
3	.354	.197
4	.453	.295
5	.551	.394
6	.650	.492
7	.748	.590
8	.846	.689
9	.945	.787
10	1.043	.886
11	1.142	.984
12	1.240	1.083
13	1.339	1.181
14	1.437	1.280
15	1.535	1.378
16	1.639	1.476
17	1.732	1.575
18	1.831	1.673
19	1.929	1.772
20	2.028	1.870

SPECIFICATIONS

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC, DC
 Poles: 2-20
 Material: Nylon 66 UL94V-0
 Insulation Resistance: 1000MΩ min.
 Applicable Wire: AWG #28-22
 PCB Thickness: .047", .063"
 Color: White, White-Ivory
 Withstanding: 800V AC
 Temperature Range: -25C to +85C

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/09/07
				Checked	Lizzy	02/09/07
				Drawn	Tina	02/09/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-1137A-XX**

Description: 0.98" Pitch Board-in Connector Housing