

## **HEADERS & RECEPTACLES**





✓ Activ



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

E.I.S 2P POST ASSY GREEN (V)

El Series | El Series

6-171825-2

TE Internal Number: 6-171825-2

Always EU RoHS/ELV Compliant

Centerline 2.5 mm [ .098 in ]

Number of Positions 2

PCB Mounting Orientation Vertical

PCB Mounting Style Through Hole

Number of Rows 1

**Product Drawings** 

POST HEADER ASSY (VERTICAL) AMP EI SERIES CONNECTOR

PDF **English** 

CAD Files

Customer View Model

2D\_DXF.ZIP

Customer View Model

3D\_STP.ZIP English

Customer View Model

3D\_IGS.ZIP **English** 

3D PDF PDF English

**Product Specifications** 

**Product Specification** 

AMP Mass-Termination "EI" Series Connector

TIF English

AMP Mass-Termination "EI" Series Connector

PDF **English** 

AMP El Series, Connector

TIF Japanese

AMP El Series, Connector

PDF **Japanese** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Product Type	Connector
	Connector Type	Header
	Strain Relief	Without
	Profile	Low, Standard
	Connector Style	Plug
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	2
	Number of Rows	1
	Number of Positions Applied	2
	Backwall/Post Interruptions	Without
Electrical Characteristics	Operating Voltage (VAC)	250
Body Features	Header Type	Shrouded
200, 100,000	Circuit	Standard
	Circuit	
Contact Features	Contact Mating Area Plating Material	Tin over Copper
	Contact Type	Pin
	Solder Tail Contact Plating Material	Tin over Copper
	Contact Termination Area Plating Thickness (µm)	.8
	Contact Current Rating (A)	3.5
	Contact Shape	Square
	Tail Plating Material	Tin
	Contact Termination Area Plating Material	Tin
	Contact Base Material	Brass
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Alignment	Without
	Mating Retention	With
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Contact Retention	Without
	Mating Alignment Type	Polarization
	wating / ingriment Type	Folarization

	Mating Retention Type	Polarized Lock
Housing Features	Centerline  Housing Color  Housing Material	2.5 mm [ .098 in ]  Green  6/6 Nylon
Dimensions	Tail Length Wire/Cable Size (mm²)  PCB Thickness (Recommended)  Wire/Cable Size (CMA)	3.6 mm [ .142 in ] .0833 1.6 mm [ .063 in ] 159.8 - 642.4
	Mating Post Length  Height  Wire/Cable Size (AWG)	7.5 mm [ .295 in ] 10.4 mm [ .409 in ] 28 – 22
Usage Conditions	Operating Temperature Range (°C)	-20 – 95
Operation/Application	For Use With Pick and Place Cover	Receptacle Assembly Without
Industry Standards	UL Flammability Rating  CSA Certified  Agency/Standard	UL 94V-0 Yes UL
Packaging Features	Packaging Method Packaging Quantity	Bag/Box 1000
Product Compliance	Statement of Compliance PDF  VIEW ALL PRODUCT COMPLIANCE	





PRODUCT - MATING PRODUCTS

Connectors - Wire-to-Board Connector Housings El Series | El Series

REC HSG LOW PROFILE EI 2P - 6-172142-2 TE INTERNAL NUMBER: 6-172142-2

✓ Active

Not reviewed for RoHS

Compliance

Centerline 2.5 mm

Number of Positions 2

Number of Rows 1

Color Green

Mating Retention With

