



TYPE 2

SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2502WR-02P2	2.50	7.50
A2502WR-03P2	5.00	10.00
A2502WR-04P2	7.50	12.50
A2502WR-05P2	10.00	15.00
A2502WR-06P2	12.50	17.50
A2502WR-07P2	15.00	20.00
A2502WR-08P2	17.50	22.50
A2502WR-09P2	20.00	25.00
A2502WR-10P2	22.50	27.50
A2502WR-11P2	25.00	30.00
A2502WR-12P2	27.50	32.50
A2502WR-13P2	30.00	35.00
A2502WR-14P2	32.50	37.50
A2502WR-15P2	35.00	40.00

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	
DRAWN BY	APPROVED BY	2.50mm PITCH 90° WAFER, TYPE 2	
李勤	董正一		
2006.05.14	2006.05.14		
GENERAL TOLERANCE			
		X. X±0.25	ANGLE±
A0	NEW RELEASE	2006.05.14	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
			DRAW NO. : A2502WR-XP2
			REV. A0