



RECOMMEND P.C.B. LAYOUT
BOTTOM VIEW

MATERIALS

- 1. HOUSING : P.B.T. (UL 94V-0), BLACK.
- 2. TERMINAL : S.Q. 0.64mm BRASS, GOLD PLATING.

SPECIFICATION

- 1. CURRENT RATING : 3 AMP. MAX.
- 2. DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC R.M.S. FOR ONE MINUTE.
- 3. INSULATION RESISTANCE : 5000M OHMS MIN. AT 1000V DC.
- 4. OPERATING TEMPERATURE : -55°C TO +105°C.

NUMBER OF POSITION	DIMENSIONS			NUMBER OF POSITION	DIMENSIONS		
	A	B	C		A	B	C
6	15.24	12.94	5.08	26	40.64	38.34	30.48
8	17.78	15.48	7.62	30	45.72	43.42	35.56
10	20.32	18.02	10.16	34	50.80	48.50	40.64
12	22.86	20.56	12.70	40	58.42	56.12	48.26
14	25.40	23.10	15.24	44	63.50	61.20	53.34
16	27.94	25.64	17.78	50	71.12	68.82	60.96
20	33.02	30.72	22.86	60	83.82	81.52	73.66
24	38.10	35.80	27.94	64	88.90	86.60	78.74



PART NO. B-D-xx

DWG NO. B-D-xx

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE
X ± 0.3
XX ± 0.2
XXX AWG

DESCRIPTION: 2.54mm SHROUDED HEADER P.C.B MOUNT VERTICAL

煜倫有限公司

UNIT / mm

SCALE 1:1

PROJECTION

AREA	REVISIONS	HK	DATE
------	-----------	----	------