



**MATERIAL**  
 Insulator : 30% Glass fiber PBT  
 Contact Pin : Brass

**SPECIFICATION**  
 Current Rate : 1 AMP  
 Insulation Resistance : 5000MΩMin. at DC 500V  
 Contact Resistance : 20mΩMax. at DC 100mA  
 Dielectric Voltage : AC 500V for one minute  
 Operation Temperature : -40°C to + 105°C

- 1. : Dual rows  
     Plastic Height=1.5mm  
     : Dual rows  
     Plastic Height=2.0mm
- 2. No. of contacts per row
- 3. G: Gold flash  
     T: Tin plated
- 4. B: Black Insulator
- 5. Pinrex internal code.

CODE	DIM A	DIM B	DIM C	DIM D
M-RB15-2Xxx	3.90	2.80	2.50	1.50
M-R-2Xxx	3.90	2.80	3.00	2.00

If you need other dimensions,  
 please fill out Dim A/B/C or  
 contact our sales representatives.

DIM A	DIM B	DIM C	DIM D

POLES	DIM E	POLES	DIM E
		23	44.00
2	2.00	24	46.00
3	4.00	25	48.00
4	6.00	26	50.00
5	8.00	27	52.00
6	10.00	28	54.00
7	12.00	29	56.00
8	14.00	30	58.00
9	16.00	31	60.00
10	18.00	32	62.00
11	20.00	33	64.00
12	22.00	34	66.00
13	24.00	35	68.00
14	26.00	36	70.00
15	28.00	37	72.00
16	30.00	38	74.00
17	32.00	39	76.00
18	34.00	40	78.00
19	36.00	41	80.00
20	38.00	42	82.00
21	40.00	43	84.00
22	42.00	44	86.00

**MORETHANALL**  
 CONNECTORS  
 ASSEMBLIES

焯倫有限公司

PART NO. M-R-2Xxx  
 DWG NO. M-R-2Xxx  
 FILE NO.  
 UNIT / mm      SCALE 1:1

APPROVED BY CY  
 DRAWING BY  
 PROJECTION

TOLERANCES ARE  
 .0 = ±.30  
 .00 = ±.20  
 .000 = ±.XXX  
 .0000 = ±.  
 ANG. = ±3°

DESCRIP TION: PIN HEADER 2.00\*2.00mm  
 RIGHT ANGLE TYPE, DUAL ROWS

AREA	REVISIONS	HK	DATE